

AVIATION WEEK

A MCGRAW-HILL PUBLICATION

AUG. 8, 1955

50 CENTS



No paper tiger

For keeping peace, some call our country a paper tiger. They err. Our strength, like the Navy's new F11F-1, is not on paper. This Tiger by Grumman is real. This Tiger is small and supersonic and will prey on enemies if attacked. To be ready in quantity when needed, Grumman designed and built the first Tiger in 15 months. Until Tigers join the fleet in quantity, Grumman Cougars will help the Navy police the sky and keep peace.




GRUMMAN AIRCRAFT ENGINEERING CORPORATION

BETHPAGE • LONG ISLAND • NEW YORK

DESIGNERS AND BUILDERS OF SUPERSONIC TIGERS, TRANSONIC COUGARS, S2F SUB-KILLERS, ALBATROSS AMPHIBIANS, METAL BOATS, AND AEROBIOT TRUCK BODIES

First in Constant Speed Drives...



NOW...longer life for Sundstrand Constant Speed Drives

Here are figures gathered from Sundstrand Constant Speed Drive performance in the D 36 and T5M. Similar records are being established daily in other types of aircraft. Much of the credit for longer life goes to Sundstrand service representatives stationed throughout the Free World to provide Sunon with the Air Force, Bureau of Aeronautics, engine and airframe manufacturers. These men aid in design of new applications... help with modifications... train personnel in maintenance, operation, and trouble shooting... supervise tests in the field. For experienced counsel on your Drive System problems, call on us today.

OVER 6500 drives in the field

•
AIR FORCE T-28 now permits
1000 hours logged flight time
between overhauls

•
1200-1700 hours logged
flight time accumulated by many
drives on Navy aircraft

SUNDSTRAND AVIATION

Division of Sundstrand Machine Tool Company, 1000 FORD, ELK GROVE, ILLINOIS Western District Office, Hawthorne, California

CONSTANT SPEED DRIVES • AIRCRAFT ACCESSORIES



SHOWN IN FLIGHT TO THE UNIVERSITY OF CALIFORNIA, BERKELEY, CALIFORNIA

One of the few things that fly
that couldn't be made better with
3M Adhesives, Coatings and Sealers



For a free booklet (showing 3M Adhesives, Coatings and Sealers at work in the aircraft industry, write today to 3M, Department 24, 417 Pageant Avenue, Detroit 2, Michigan. For even faster facts, call in your 3M Field Engineer.

ADHESIVES AND COATINGS DIVISION MINNESOTA MINING AND MANUFACTURING COMPANY



The forgings illustrated are typical of the large Aluminum Alloy Airplane parts in current production on the heavy presses at Wyman-Gordon.

A new era in the art of forging has been demonstrated as production goes forward on this 35,000-ton closed die forging press. Longer forgings with thicker sections and closer tolerances than heretofore possible open new concepts in forging design. Wyman-Gordon continues to pioneer by — Keeping Ahead of Progress.

WYMAN-GORDON CO.

Established 1883

FORGINGS OF ALUMINUM • MAGNESIUM
STEEL • TITANIUM

WORCESTER 1, MASSACHUSETTS
HARVEY, ILL. • DETROIT, MICH.

NEWS DIGEST



ANTI-NUCLEAR part for atomic weapons covers air shown on the belly and nostrils of this Boeing B-52 Stratofortress. First is designed to select the best of a nuclear explosion after the long wings have blasted under its drop. The B-52 is undergoing flight tests at Boeing's Seattle plant prior to delivery to USAF's Strategic Air Command. Stratofortresses, equipped with eight Pratt & Whitney A4000 37 jet engines and aerial refueling gear, also are in production for the Air Force of the Young Republic (Kai) Division.

Domestic

President Eisenhower signed the new \$232-million airport construction bill after Commerce Undersecretary Loren R. Hefschel reportedly advised against a veto. The new law authorizes \$61.5 million in federal aid available this fiscal year. Airport experts estimated there is nearly \$200 million in local funds available now to match federal money.

First jet transport to be certified for commercial U. S. airline operations available will be Boeing Airplane Co.'s Model 707 series. The new and Civil Aeronautics Administration last week for a type certificate on the aircraft as an initial step in approval of an airline version, among the prototype 727. Strickland has accumulated 191 flight hours and tests on models the aircraft safety level defined by Civil Aeronautics Regulation 4b. Boeing received USAF permission last month to build commercial jet transports with the KC-135 fuselage, military version of the 747 (AW July 18, p. 14).

Eastern Air Lines ordered 20 additional Douglas DC-7Bs. The new order will give EAL an ordered fleet of 80 DC-7Bs. Eastern has taken delivery on five of the first 20 planes ordered; expects to receive the next 15 within 12 months and the final 10 between October 1947-October 1957 and April 1958.

Lt. Gen. Christina F. Schell has been appointed Assistant Commandant of the Marine Corps for Air, succeeding Lt. Gen. William O. Brice.

Lockheed Aircraft Corp.'s Marietta, Ga., plant completed on schedule its last contract for Boeing B-47 "jet parts." The 3,000 on-line deliveries created more than 4 million individual parts.

Chance Aircraft Co., wholly-owned subsidiary of Walrus Motors, Inc., has been retained Kinair Aircraft & Electronics Corp.

Control and test equipment for guided missiles will be manufactured by International Telephone & Telegraph Corp.'s Fairchild Electronics Co. of Fair Wayne, Ind., under a new \$50 million contract.

Financial

North American Aviation's net income for the year ended June 30 totaled \$21,615,000, increasing sharply from \$14,725,000 for the same fiscal period last year. Sales and income amounted to \$550,378,825. Backlog of unfilled orders as of June 30 \$1,346,108,122, compared with unfilled orders of \$1,066,243,552 as March 31.

Bell Aircraft Corp. earned a net income of \$5,153,977 for the six months ended July 3, compared with \$5,419,536 first half of last year. Sales increased to \$107,861,750 from \$93,297,849. Unfilled orders as of July 2 totaled \$285 million.

Boeing Airplane Co. reported net earnings of \$33,855,510 from sales totaling \$576,181,711 for the first half of 1953, dropping from a \$27,548,648 net and sales of \$496,581,262 during the similar period of 1954. Backlog of orders June 30 amounted to \$1,980 million, compared with \$2,111 million at the end of last year.

Chance Vought Aviation's net income for the first half of the year dropped to \$2,253,063 from \$3,209,586 for the same period of 1954. Sales totaled \$29,011,774, compared with \$27,666,640. Unfilled orders, including letters of intent, declined to \$182,780,000 on June 30 from \$193,128,000 on March 31.

International

Solovs Reliance Airlines is negotiating with Russia for a route to Moscow, according to reports. Solovs would operate the proposed Brussels-Moscow route as an extension of its present service to New York.

From
wrapping bread
to
launching
missiles...



Designing and producing intricate bread wrapping made easy, or developing guided missile launching equipment...such demands advanced technology. And there are but two of the hundreds of complex tasks the AMF organization performs every day. The highly specialized yet widely diversified activities of some 85 engineering and production



facilities provide AMF with a wealth of experience that covers nearly every field of industry. And it is increasingly available to you.

Call upon AMF with your problem. See why this all-around experience in answering the needs of government and industry has made AMF the "can do" company.

AMF HAS EXPERIENCE YOU CAN USE!



AMERICAN MACHINE & FOUNDRY COMPANY, Defense Products Group, 105 N. Royal Street, Alexandria, Virginia
Executive Office—AMF Building—24 Madison Avenue, New York 15, N.Y.

Washington Roundup

R & D Headquarters

Air Force is standing in its decision that headquarters for the Air Research and Development Command should be located at Wright-Patterson AFB headquarters for the Air Materiel Command. Two recent studies made under the direction of Lt. Gen. Thomas Power, research and development commander, endorse the Dayton location. One was by the nonmembers of research and development institutions and the other by a private industrial management firm.

"Dayton is the right location," Assistant Secretary of the Air Force for Research and Development Tyrone Goshaw declared. "When Congress comes back in June we will make a merit effort to convince them of that." (See p. 18)

Air Bilaterals

The Senate Commerce Subcommittee, headed by Sen. George Scriven (D-Fla.), will propose hearings shortly on the U. S.-German bilateral agreement and the facts surrounding its negotiation. Scriven has vigorously protested it, claiming the U. S. gave too much and got too little. Later the subcommittee will go on to other bilaterals. A main object of the investigation is to decide whether legislation giving the Senate veto authority over executive agreements should be pushed when Congress reconvenes.

Symington on Tolbert

USAF's first secretary, Sen. Stuart Symington, said, but didn't succeed, in keeping out of the conference over USAF Secretary Harold Tolbert, a personal friend. Symington's sole original comment: "He has done a fine job for the Air Force."

Symington's, however, Oregon Sen. Wayne Morse pointed to Symington's speech as evidence that "even on the basis of Mr. Tolbert's record as Secretary of the Air Force, he ought to be dismissed irrespective of his conduct."

Symington explained his original brief comment: "What I had in mind was just this Secretary Tolbert presented with ability and energy to the Congress the one for an expanded Air Force."

Army Air Control

U. S. Army continues to move quietly in the direction of more independence control over its aviation. Several more reorganizations of the Board No. 6, Commanded Army Command I is a new development and test agency for aircraft located at Camp Rucker, Ala., home of the Army Aviation School. Activity formerly was under COMARAC Board 5, which embodied communications, electronics and airborne equipment as well as troop land units. More is connected with establishment early this year of separate Army Aviation Division of G-3, located in Bag Camp. H. H. House.

CAB and Congress

Regulations reorganization of continually strained relations between Congress and the Civil Aeronautics Board led to the newly created CAB post of Congressional Liaison Officer, which has been filled by Arnold Kruger, 51, former member of the GOP National Committee staff.

Although most CAB squabbles with Congress have been aimed at what Russ Bailey, Senate Board chairman this year, Kruger is expected to initiate a proposed reorganization between the regulator agency and its parent body.

Major complaint of lawmakers is the past has been with the Board's delay and convenience in reviewing requests as well as poor preparation for hearings. Kruger, who will report directly to Kruger, served as secretary to Rep. H. C. Loefer (R-S. Dak.), and later at the Department of Agriculture.

Wilson's Order Ignored

Defense Secretary Charles E. Wilson's order directing the armed services to replace generals and admirals with civilians as chiefs of their public information offices (AW Apr. 4, p. 11) has been quietly ignored.

Last week the Navy, headed-up by many months by the fact that Rear Adm. William G. Brehm, Jr., chief of public information, has been ill, named another admiral to replace him. New chief is Edmund B. Taylor, Pacific destroyer base and Avonport harbor side of the early 1970's. Indications are that Adm. Taylor, who has served in the Pentagon in a side to both the Secretary and Under Secretary of the Navy, will move in with minimum fanfare and no mention of the fact that Mr. Wilson once demanded that his chair be filled from outside military circles.

Meanwhile, the Army still must make a decision along the same line. Its top PIO, Maj. Gen. Glavin C. Mudgett, is being asked to a new command at Fort Gil, Calif. His deputy, Brig. Gen. T. S. Rags, temporarily will head the public information office.

Third military man who was supposed to move out under the Wilson order is Brig. Gen. Robert Lee Scott, USAF. He had been on his job only a few days when the Defense Secretary closed down, but managed to continue with considerable success and was his last stay in the service.

ASPR Revision

Defense Department is maintaining silence on aircraft industry's mounting criticism of the proposed revision to Section XV of the Armed Services Procurement Regulations (AW Feb. 4, p. 14). Indications are that meeting to discuss differences will not be held until sometime in late October. Meanwhile, the aircraft industry is eager to learn the attitude of Dudley C. Sharp, who will replace Roger Lewis as Assistant USAF Secretary for Materials on Oct. 1, toward cost-allocation of companion plan involving profit cuts and stock bonuses. Lewis' place on such items with a cold eye, viewed more in contractual situation industry hopes Sharp "will be more realistic."

Aircraft Investigations

The plan now of two congressional committees—House Appropriations Subcommittee on the Armed Services and House Armed Services Investigative Subcommittee—is to put off hearings on profits of aircraft and other defense contractors until the new session next January. Staff work will be completed during the recess. "What the staff comes up with will determine what we will do then," Rep. George Miller (D-Calif.), chairman of the Military Appropriations Subcommittee, said.—Washington Staff

Air Force Eliminates Design Studies

Aircraft firms will be chosen for Phase I contracts on basis of performance to speed new developments.

By Claude Witte

Washington, D. C.—U. S. Air Force has revised its weapons system proposal procedure to eliminate preliminary design studies, substituting Phase I contracts with a small number of limited-cost aircraft concepts.

To the U. S. Air Force, this means increasing emphasis will be placed on pre-performance, know-how, the availability of engineering effort and current work load. On the basis of these factors, USAF will decide which companies will be awarded to design weapons and support concepts for evaluation.

USAF introduced the new procurement philosophy last week when it awarded Phase I development contracts to six manufacturers for three different types of aircraft, a long range interceptor, a fighter-bomber and a tactical bomber.

In the case of the long range interceptor, a design competition was held and recommendations were sent to the Air Staff by the Air Research and Development Command and the Air Materiel Command.

However, no decision was reached on the basis of the "paper designs." Result was awarding of Phase I contracts to four firms.

Advantages Cited

USAF is confident the award process will attract these goals:

- **Conservative engineering** encourages the dominating right to twice design studies, most of which never exist as hardware.
- **Competition development** ends of new weapons. This is a field in which Russia has made tremendous strides, coming up with improved aircraft much quicker than anticipated by aircraft experts in the U. S.
- **Improve chances** of obtaining a good product that will fit USAF's needs.
- **Save money.** Some USAF officials have noted making an error of the fact that picking a weapons system from paper proposals has resulted in growing delays and development headaches higher costs and disappointing returns with the industry.

"The new approach," one of them

told AVIATION WEEK, "is to see the cost, not place the bet from the racing firm."

Industry Reaction

While the new system will not call for killing prototypes, company representatives feel the USAF decision is a step in the right direction. There has been growing dissatisfaction with the procedure of awarding production contracts for a single design prior to flight of a prototype.

"The competitive system is by far the best," one company official told AVIATION WEEK, "but in practice, of course, only during a period of intense world tension when it is not necessary to risk producing designs into aircrafts whose production without a competitive test."

The decision no longer is to USAF to place proposals is not expected to have any effect on utilization of the Cost-Share plan to speed output into the weapons system is ready for production.

The shift in choosing design studies is to company development from the field in which USAF has been feeling pressure from its Red air force rivals.

Industries that a change to procure more policy in the design and development stage have been reacting in several ways.

Specialization Factor

In an interview with AVIATION WEEK, Roger Lewis, senior Assistant Secretary

of Air Force for Materiel, said that tough competition was ahead for the aircraft industry, with increasing emphasis on the individual firm's past performance (AW No. 15 p. 15).

Later, in testimony before a subcommittee of the House Committee on Appropriations, Lewis placed emphasis on the specialized nature of airplanes and the companies who design and make them.

"We have about 12 airplane companies which have the engineering organization and production resources with which to design and develop an airplane," Lewis told the House committee.

"But there among the 12 companies there is a high degree of specialization which limits the field."

For example, he has only two companies which have had experience, and have the competence to develop heavy bombers. We have three or four companies that can develop fighters. And we have some other companies that can develop transports and cargo planes.

"So among the 12 there are only two or three that really compete directly with each other on specific items."

This conviction, it was clear last week, has led USAF to discard the system under which a design firm competes as preliminary design work, winning a great deal of the nation's aircraft engineering talent, without producing an idea of making hardware for evaluation.

Lewis played a major role in the decision to change the procurement policy.

"We are involved in this by the new Design Cost of Share for Materiel," Mr. Gen. Clarence S. Brown, former deputy commander of AMC for production.

Senate Approves Sharp

The Senate unanimously confirmed the appointment of Dudley Sharp, Houston oil equipment manufacturer, as Assistant Secretary of the Air Force for Materiel.

He succeeds Roger Lewis whose resignation becomes effective Sept. 30 (AW July 25, p. 15).

It is understood that Sharp was recommended by Robert Anderson, a Defense Times, who recently resigned as Deputy Secretary of Defense.

Long Range Interceptor Contracts Among New Policy's First Awards

By William J. Connelley

Los Angeles—Air Force awarded six development contracts last week for three different types of aircraft—a long range interceptor, a fighter-bomber and a tactical bomber.

Phase I preliminary designs and mock-up contracts went to North American Aviation, Northrop Aircraft and Lockheed Aircraft Corp. for the long range interceptor, Republic Aviation and North American received similar contracts for a fighter-bomber and Glenn L. Martin and Douglas Aircraft were awarded development contracts for a tactical bomber.

Final Air Force decision on the new series of aircraft will await evaluation of the proposals.

In the case of the long range interceptor, USAF has been considering designs studied submitted over months ago by a number of weapons system contractors. The fighter-bomber and tactical bomber will be new aircraft and the aircraft companies selected for Phase I contracts do not have previous proposals at the present time.

Here are the winning entries in the long range interceptor competition.

• **North American** submitted an advanced version of its forthcoming F-103B, originally designated the F-103B and designed for Mach 2 speed while the NAA proposal is similar to the F-107, it is regarded as a "probably new weapon."

• **Northrop design** is its modified Delta Scorpion, a delta-wing F-99.

• **Lockheed proposal** is an entirely new aircraft wing design. It is not a version of the aircraft fighter F-104.

Air Force specifications for the new interceptor call for Mach 2 speed and a combat radius of 1,000 miles. The new tactical aircraft would weigh about 30,000-35,000 lb.

Outlets Requirements

Designated mission is that of a long-range interceptor designed to intercept and shoot down enemy strategic aircraft, rather than to intercept other fighters. The long range interceptor will be armed with air-to-air missiles.

No drivers were developed as the previous line contract and suggested equipment to be used.

With specifications exchanged since the request for design proposals was made in the fall of 1975, Air Force Command is said to believe the performance outlined for the new LR2 aircraft does not fit the requirements for

the time period in which it would become operational. The indicator that evaluation of latest Russian aircraft has placed their performance much higher than previously anticipated.

One industry source predicted that while the contract design studies are being carried out, a requirement will be needed for a higher performance airplane and re-submitted to industry. It said it is unlikely that one of the three interceptor entries will ever be built or squared.

F-101 Voodoo's Role

Air Force is going ahead with plans for a larger version of McDowell Aircraft Corp.'s F-101 Voodoo as an air defense long range interceptor to meet defense requirements within five years.

While the Voodoo was undergoing flight tests at Edwards Air Force base, an observer flew in the company of a Voodoo at a "good aircraft which is doing well."

Large enough to have the major version, the modified F-101 will be able to carry the best fire control equipment available. The aircraft can be operated within three years, according to estimates in time to meet a critical need in the balance of strength between the United States and the Soviet Union.

First place in the technical evaluation of the long range interceptor proposals went to Lockheed, with Boeing Aerospace Co.'s Walrus Division a runner-up. The Voodoo was not a contender, but may have been left out of the contract award due to a feeling that it is now fully accepted in the jet bomber, tanker and transport fields.

General Dynamics of General Dynamics Corp., once a top contender in the competition with a version of the B-58, cannot be regarded as entirely washed out of the long range interceptor picture by award of the design contracts.

The B-58 is scheduled to be by the fall of next year and, while reliable sources report that this fast aircraft will be only an "airborne theater," it will enter into the first Air Force interceptor defense.

In announcing its report that pre-planning is being held up to study possible developments now entering the design phase, it will be a "Mach 2 aircraft" which is being considered; The rest to talk to, to see, one of the Air Force is industry who is loath to change to believe a missile will do the job.

Among important factors working in favor of the F-101 and against are discussions to build a prototype version

Weapons Lab

The establishment of a new weapons development laboratory at the Wright Air Development Center, Dayton-Fairborn Air Force Base, Ohio, through the expansion and reorganization of the former Avionics Laboratory was announced last week by the Air Research and Development Command.

The Weapons Effects Branch of the new laboratory takes over the activities formerly assigned to the Avionics Research Laboratory and the Avionics Development Laboratory. Other branches whose work has been integrated into the new laboratory include the Guidance Development Branch of the Avionics Research Laboratory and the Communications Navigation Laboratory.

- **Intelligence reports** indicating the Russians will have a supersonic bomber fleet operational in the 1980's, which would make the performance of this interceptor of major importance.
- **Need for an aircraft** to meet the Red threat in the second year to 1980.
- **Stability of the aviation industry** to provide for control and guidance equipment to match the speed of the aircraft at the time it actually was scheduled to start in production.
- **Lack of personnel** required by the high performance aircraft.
- **Reduction that design** is the competition, was hampered by a significant requirement that was necessary.

"Air Force had others around that this aircraft would struggle with other aircraft, it is a top priority effort," it was implied in the report and the aircraft therefore compromised the job of "battlefield interceptors."

An aircraft is intended to defend the continental United States from Soviet bombers at a distance of 1,000 miles from U. S. borders will not have to maintain fighter, but not.

"USAF is actually come to the realization that the case is for a bomber-interceptor, not a fighter-interceptor. All the companies in the industry know that all along but we just didn't face up to it."

More top Air Force officers now believe a main purpose need to for an aircraft that can defend the U. S. against bomber planes in 1980.

Such an aircraft will not have to be a Mach 2 aircraft, but it will have to be, if not all, of the Red bomber fleet will be subsonic in the period.

Modification of an existing aircraft could meet these requirements. The work will be supported for this task in the F-101, according to USAF.



Bison Details Shown by Navy Model

First design details of the B-36, Boeing's ultracontractual heavy bomber, are shown in this official engineering model built from related intelligence data by the Special Devices Center (Office of Naval Research).

Features of the B-36 bomber not previously disclosed in pictures of the plane in its several public appearances over Moscow include:

- Flexible landing gear like the Boeing B-27, with outrigger gear in wingtip pods.
- External fuselage dorsal and ventral bomb bays, carrying 10-ton bombs and missiles, including a launch state of the atomic art in Russia that here.
- Conventional control system for all three axes in contrast to the spoilers, split rudders and other schemes used

in contemporary U.S. aircraft.

- Canted intakes for the 16,000-hp thrust turbojets to allow for an intake near the fuselage and the inboard nacelle, evidence of subsonic nacelle intakes to require flow characteristics.

Aerodynamic Layout

Bison's wing is curved slightly at the leading edge, with the greatest degree

of sweep ahead. Thickness tapers an evenly, too, with higher rates released of the wing trunk.

The Navy model shows a single main spar, with secondary spars at the leading edge and ahead of slats and flaps. Ailerons and flaps appear to be about 10% of wing chord; flaps are single slotted type.

A single horizontal trim flap is fitted to the top of each panel just ahead of the aileron root.

The fuselage is elliptical in cross-section. The belly line is straight, interrupted by a ventral turret and a thin bomb bay intake. The upper fuselage line is a long, graceful curve, bending downwards at each end and giving the nacelle a dropped appearance. Forward of the turret position, the fuselage also tapers in planform.

Ventral and horizontal tails are swept and have the geometry characteristic of Douglas's latest designs. Bomber has a very wide chord, contrasting with the much smaller chord of the ailerons.

The tail turret has windows, and is shown occupied in the model above. It is a unique type of remote-control turret.

Indicators of production locale on the Navy model point to the external construction of wing center section and horizontal main. The wing outer panels attach just inboard of the outboard nacelle rather than at the back of the trailing edge.



Skis Add Flexibility to C-123

Stearns Aircraft Corp. has mounted a C-123 aircraft mounted on retractable hydro-skis, turning it into an amphibian that could use U. S. Air Force battle supply lines from the necessity of operating out of airports.

Sacrificing less than three miles an hour of the aircraft's cruising speed, Mike Stearns, president of the company, claims he has opened up most of the world's surface as a landing area for aircraft.

This covers not only the sea and lakes but surfaces covered by snow, sand and ashfall craters.

The new landing gear, called Ponto, has been developed under contract for the Air Research and Development Command. It consists of two reinforced hollow skis that can be folded into the hull of the aircraft during flight or operation on conventional gear from an airport.

Other modifications to make the Pontoise YC-123E include a piston on each wing, strengthening and water-tight treatment for the hull, plans a fuselage and a slight solution in the direction of the Hercules-Stearns proposal.

Blade-Thrust Car

The props were changed to provide clearance when the aircraft is taking on water.

Stearns' blade-thrust car has been cut from approximately 3,900 lb. to about 3,600 lb. Conventional transport version of the plane, the C-123B, is being manufactured by Fairchild Aircraft Division, Hagerstown, Md.

At a demonstration of the Pontoise plane in Philadelphia, Stearns told Aviation Week he has an USAF contract for ten more aircraft. These will combine the hydro-skis landing gear with Stearns' latest control features.

Pontoise YC-123 Specs

Dimensions:	
Wing span	120 ft.
Length	77 ft. 2 in.
Height	22 ft. 10 in.
Area:	
Wing	3225.2 sq. ft.
Fuselage int.	389.3 sq. ft.
Vertical int.	179.8 sq. ft.
Weights:	
Weight empty	34,000 lb.
Design useful load	10,000 lb.
Design gross weight	44,000 lb.
Capacities:	
Cargo	14,000 lb.
Trips	41
Cargo compartment dimensions:	
Length	36 ft. 8 in.
Width	9 ft. 2 in.
Height	5 ft. 2 in.
Performance:	
Cruising speed	170 mph
Range	1,300 miles
Take-off, water	1,400 ft.
Take-off, land	500 ft.
Landing, water	750 ft.
Landing, land	1,000 ft.

currently being tested on another prototype, the XC-123D at Stearns' plant in Tucson, N. J.

Adoption of the Pontoise idea to other USAF transports so that they can take advantage of terrain flexibility is limited only by budget, according to ARDC spokesman.

Fuselage Retrofit

The hydro-skis are to be put on any high-wing plane where the fuselage is clear of the water and the aircraft's belly can be modified to be watertight and stable while floating.

In the case of the C-123, the ac-

design of the fuselage did not interfere with the spaceframe of the cabin as the straight-in tail loading ramp.

The YC-123E is the same aircraft that Stearns' first flew in the late 1940's as a glider. Later, four General Electric J-87 jet engines were installed and it became the first jet-powered cargo plane. For the Pontoise experiment, the water buoyant hull of the design was rebuilt in addition to adding the wing tip floats.

Congress Cuts USAF Construction Funds

The \$1.678 billion approved for fiscal 1956 construction of Air Force installations is \$122 million less than USAF's \$1.2 billion request.

Congress on two controversial issues, took three actions:

- Eliminated \$5 million for a new headquarters building for the Research and Development Command. Those was general agreement on the requirement for the headquarters. But congressmen were skeptical of USAF's plan to locate it at Wright-Patterson AFB. Other Service Armed Services Committee has directed USAF to reconsider.

- Voted \$20 million for USAF's new Air Force Academy, with a fourth of the \$70 million USAF requested. Congress decided that "goldplating" construction could save money while USAF decides on the architectural design. The site, moderate design originally planned by USAF precluded much redesigning.

USAF's \$1.078 billion was the major portion of the total \$2.007 billion Congress approved in new money and transfer funds for fiscal 1956 military construction.

The Army was voted \$407 million, Navy, \$442 million.

The \$254 million cut from the total \$2.373 billion added by the three services was divided: USAF, \$222 million; Army, \$60 million; Navy, \$56 million.

Major projects in the USAF program include:

- Air Defense Command: Greater Missiles, com. \$16.6 million
- Air Materiel Command: Office AFB, N. Y., \$14.8 million; Wright Patterson AFB, \$11.6 million
- Research and Development Command: Arnold Engineering Development Center, Tenn., \$13.4 million; Bedford Com. research center, \$22.4 million
- Military Air Transport Command: Charleston S. C., AFB, \$10 million
- Strategic Air Command: Chertkov River near GUL, AFB, \$10.2 million; Des Moines, AFB, \$11 million; Ellsworth, S. D., AFB, \$21.4 million; Fairbury, N. Y., AFB, \$22 million; Portsmouth, N. H., AFB, \$24.5 million

Guiding or intercepting



Research, development, production of electronic computers for defense



Today our Armed Services are making valuable use of Burroughs Corporation applied research for analysis and study of assigned defense research, of our expert engineering for development and testing of prototypes and of our micro-process manufacturing facilities for final production of defense appliances.

Burroughs' defense accomplishment embraces the fields of instrumentation, control systems, communications, integrated and electronic components and electronic computers. It is marked by achievements like the A-4 Gun Sight, the Skywarrior "brain", ground guidance computers for high-precision systems and other classified projects. Address inquiries to Burroughs Corporation, Detroit 32, Michigan.



Burroughs

BURROUGHS INTEGRATED DEFENSE FACILITIES INCLUDE:
Burroughs Corporation plants in Detroit and Plymouth, Michigan
Burroughs Electronic Systems Division, Philadelphia, Pa.
Honeywell Division, New Jersey, Philadelphia, New Jersey
Orbit Instrument Company, Springfield, New York
Burroughs Research Center, Palo Alto, Calif.



YC-123E supply plane designed to operate from water and unimproved landing strips.



HERCULES' cargo doors are open for air dropping supplies to Army troops.



TN-40 M108s outside the side of the C-130 for delivery to a TAC landing site.



CARGO DOORS open up and down with bottom section forming ramp up which loads in allowing an Army 105 mm howitzer.



CARGO interior is shown from rear. A 105 mm howitzer is loaded. Parachute system permits high altitude flights.



LOCKHEED's turboprop thrusters increase glide

capacity of Tactical Air Command to move U. S. Army troops and equipment and TAC's own wide base work in the 1,000 gal. fuel

C-130 Adds Versatility to TAC Airlift

Air Delivery System Parachutes Heavy Equipment Swiftly, Gently



TWENTY TONS OF SUPPLIES can be paraded from a C-130 Hercules in a few seconds using delivery system developed by Lockheed in cooperation with Fordson Tire and Rubber Co. and Bessie & Perkins Inc. Equipment and supplies are easily fastened to slings which are suspended from the aircraft.



FOUR PARACHUTES keep the cargo-laden platform reasonably level for safe landing.



AIR-FILLED BAGS made by Fordson cushion the impact. Bags fill automatically.

U. S. TIME IS NOW DELIVERING IN VOLUME
ITS NEW MODEL . . .

SUBMINIATURE PRECISION RATE GYROSCOPES

To Leading Aircraft Companies For Use in Production of Guided Missiles,
Autopilots, Antenna Stabilization, Fire Control, and Target Drones.

THE WORLD'S SMALLEST—LIGHTEST—MOST RUGGED

Developed by

SANDERS ASSOCIATES

- Long Life
- Hermetically Sealed
- High Natural Frequency
- Available in Rate Ranges From 40°/Sec. Up.

Motor voltages36 or 63V, 400 Cps.
Dampingas required
Starting time15 seconds
Resolutionwell below earth's rate
Dynamic range100,000:1
Linearity0.1% to half scale
Nominal Full Scale Output5-6 Volts
Oper. Temperature Range55° to +85°C

Rugged construction enables the gyro to withstand a wide range of environmental conditions in accordance with military specifications.

Performance characteristics of the Gyro can be modified in event one of our standard models does not fulfill your specific requirements.

STANDARD MODELS NOW AVAILABLE IN PRODUCTION QUANTITIES

Direct inquiries to:
U. S. Time, 305 Fifth Ave., New York, N. Y.

The United States Time Corporation

Main Plant—Waterbury, Conn. Branches—Little Rock, Ark.; Abilene, Texas; Toronto, Canada; Dundee, Scotland

AA Traffic Record

Nation's Airline carried more than 556,000 passengers approximately 455 million passenger-miles during June, showed in a new world's record for the low traffic during the month.

In reporting the record last week, AA, Kansas City President-Sales C. E. Spurr said the number of passengers represented a 12.4% increase over June 1974 and the passenger miles a 13.3% gain. Airfreight traffic increased 20.9%, to more than 6 million ton-miles from 4.6 million during the same period last year.

Congressmen Question CAB 'Entry' Policy

Two congressmen have pressed House Commerce Committee to open a review of Civil Aeronautics Board's administration of the 1975 Civil Aeronautics Act.

In a session with the committee, Rep. Bill Rogers (D-La.) urged the committee to give particular attention to CAB's policies on new entrants into the market.

Rep. Chet Eklund (D-Calif.) meanwhile, is a speech in the House floor called on the committee to specifically investigate CAB's decision ordering North American Airlines to cease operations.

"I feel that there is no question but that there has been a violation of the Civil Aeronautics Act," Eklund observed, "but I am not certain as to who has been the violator, considering the economic jitters laid down by the CAB. There may be a technical violation by the North American Airlines, but in terms of the broad interests of the CAA act, we have given face on down that the Board has favored the interests of Commerce and thereby put out its power to foster a government-controlled monopoly in, contrary of the federal government."

NAA Traffic Up 47%

Boeing, Calif. North American Airlines, Inc. showed a 47% gain in revenue passenger-miles in June over the same month in 1974, the largest increase of any period in the aircraft's history, the company reported. Revenue passenger-miles totaled 48,947,652 compared with 33,041,587 in June of last year.

"The success was due to the addition of new DC-10 equipment to North American's fleet and the public acceptance of the airline's lowest airfares service," company official James Polgaard stated.

another filter problem solved . . .



R-F NOISE ELIMINATED IN BENDIX VALVE ACTUATOR

PROBLEM: Bendix AirForce Corporation's Pacific Division, Northridge, California, had a serious problem of rotary electric actuator for opening valves in general. But getting a really lightweight filter to keep the water from creating radio frequency interference proved to be a real problem. Any such filter would have to be mounted on an integral part of the actuator assembly, and the required 150°C operating temperature didn't help any.

APPROACH: Bendix Pacific engineers took their problem to the Radio Noise Suppression Laboratories of the Sprague Electric Company in Los Angeles. There, Sprague and Bendix engineers negotiated in making radio interference measurements and setting up envelope and retaining provisions for the proposed filter.

SOLUTION: A filter was designed by Sprague to meet the envelope, retaining and 150°C performance needs. The filter successfully passed radio interference measurements of MIL-2-6150, MIL-1-6150, and also, the rigid requirements of MIL-3-6252A. When mounted, the Bendix filter is completely enclosed in the actuator, with the filter three-scale utilized as the center terminal strip.

PRODUCTION SCHEDULES: For these and many other filters are regularly sent by Sprague plants on both coasts. We would like the opportunity to solve your problems too. Write, wire, or phone: Sprague Electric Company, 12850 So. Western Blvd., P.O. Box 6820, Los Angeles 90, California (TECO 0-7581) or North Atlanta, Massachusetts (MIDway 3-8811).

Sprague can report will provide you with complete application engineering service for optimum results in the use of radio noise filters.

YOU CAN SPEND ON

We'll be Largest Exporter Headquarters

Engineering Design Research Development

advance'ment (ad.vans'ment), n.
promotion to a higher place or dignity; progression, improvement.

new advancements and new concepts in aeronautics and related fields now under development at Goodyear Aircraft Corporation—

mean advancement and rewarding future for qualified engineers who apply themselves to progressive research and development at Goodyear Aircraft in the following fields:

Electromechanical	Pulse Techniques
Microcircuit	Weapon Systems
Servomechanisms	Antenna Design
Electronic Packaging	Miniaturization

at Goodyear Aircraft you'll have one of the world's largest electronic computation laboratories at your disposal—and invitation to a creative future which offers security and interesting diversification!

write today for application form or send complete resume to: C. G. Jones, Personnel Department, Goodyear Aircraft Corporation, Akron 15, Ohio

They're doing big things at
GOODYEAR AIRCRAFT

THE TEAM TO TEAM WITH IN AERONAUTICS

Jets Assist C-46

Two 300-hp Pratt & Whitney T55 jet engines are helping passengers C-46s off their noses on Vero Airlines' local service trips in Brazil.

Vero President Robert M. Bohn and the small French turboprop, mounted in pods under each wing, give the transport a rate of climb of 10 feet a second or 600 feet per minute.

"The passengers like it," said Bohn. "They've been educated to know that it happens itself, why."

LAA-TWA Connect With New \$2 Fare

Los Angeles—Los Angeles Airways has inaugurated a new fare for Southern California travelers connecting with Trans World Airlines' flights.

Under the new arrangement, \$2 will be added to the regular airline fare for helicopter flights between Southern California points and Los Angeles International Airport.

Negotiations are underway with United, American and other carriers for similar fare structures.

Register LAA fare structure under

fare \$1.50 and use for \$2 fare service to and from connecting airports to L. A. International. The greater portion of difference between these fares and the \$2 ticket will be absorbed by the major airlines.

Helicopter service includes direct-attach gate connections to the passenger's waiting airplane. Tickets are issued at the passenger's city of departure.

LAA President Clarence M. Bohne says that by the end of the year helicopter service will be extended to Carson, Fontana, North Hollywood, Oxnard, Pomona, Riverside and Santa Monica.

CAA Okays Madsen Lights for DC-3s

Los Angeles—Civil Aeronautics Administration has approved installation of Madsen lights on DC-3 aircraft, designed to lessen chances of mid-air collisions by indicating direction of plane's movement, its position and altitude.

At the same time, Transwestern Air Lines has launched limited production of the airborne safety aid, and the Garrett Corp.'s Aircraft Warning Service Division has requested it is prepared to make the installation on all DC-3s.

Madsen lights consist of seven light-emitting diodes mounted on the top and bottom of the air fuselage. According to a report filed before and captioned, (AAR Inc. 14, 1954 p. 30). They were designed by Capt. Andrew Madsen, a Transwestern Air Lines pilot, and have been in use on Transwestern DC-4s for some time. United Air Lines is testing the system on a DC-6.

Aircraft reports that in a recent night test the lights could be seen, and easily identified over long back by an observer on the ground at Santa Monica Airport, 35 miles apart. In another test, the illumination has been observed in light rain at a distance of 17 miles, the company says.

Reports also indicate that the lights are so strong that in broad daylight they are easily visible for several thousand feet. Then back for 1,000 ft. a second at 10,000 ft. altitude, giving the appearance of white lines moving across the sky in the same direction in the plane.

The Madsen lights DC-3 installation, including transformer, rectifier, condenser and wiring and fuselage, weight approximately 16 lb.

Limited production of the Madsen system will be handled by Transwestern subsidiary, Aircraft Engineering & Maintenance Co., Oakland, Calif., and Otto Nelson, Toledo, producer. He also reports that research and development is being done on a model for automatic control.

Small heat cycle
for perfect soldering
every time!



See it at NECCO
San Francisco, August 30-31
Booth No. 258

New!
ZEPHYR Electronic
MICROBRAZER

Accurate control of heat with electronic timer ensures identically perfect solder joints—time after time. Minimum plugs and receptacles are easy to solder to strict military "spec" with the MicroBrazor. Elements positions of annealing and cold joints, gives virtually automatic operation for assembly line soldering. Solder replacement will be glad to show you—on your assembly line.

ZEPHYR MANUFACTURING COMPANY, INC.



FREE DEMONSTRATION
In your own plant...on your own work!

Write for free
catalog No. Z-1

ZEPHYR MANUFACTURING COMPANY, INC. Electronic Division, Dept. 22, Redwood City, Calif.	
<input type="checkbox"/> Send catalog Z-1	
<input type="checkbox"/> I'm interested in demonstration	
Name _____	
Company _____	
Address _____	
City _____	State _____



SPIN-TEST MODEL of Gloster Javelin delta all-weather fighter is dropped from balloon. Open hatch shows recovery parachute.

Farnborough Demonstrates Latest Steps in

London—Eight demonstrations of English Electric's P1 Britain's largest supersonic interceptor prototype highlighted the Golden Jubilee celebration of the Royal Aircraft Establishment at Farnborough.

A combination of static and flying displays gave a small segment of the British public its biggest look into the inner workings of its top research unit.

In the various exhibits testing and demonstrating technology were a wide

variety of displays covering every aspect of aviation development. Wind tunnel computers, larger and structural test rigs, machine shops, hangars were all open to public inspection. In a large hangar with RAE Department as well as the various air and missile, various test additional exhibits is well.

These specific items give an insight into the technological progress and direction of aviation in Britain.

Wing tip rocket pods, some with war riding holding since the early 1950s

also return carrying up to 31 smaller payloads.

- A large balloon rig with a scale model Javelin and its front-line fighter tests.
- A size "nose" shows on target.
- A shock wave and supersonic flow-flight models plus their latest results.
- Guided missile test vehicles, including various systems, replicated risk of components.
- Titanium alloy with a maximum tensile strength of 77 tons per square inch.
- Hydrodynamic tests used in solar energy test program.
- Three full-scale water tanks for pressurized engine testing, including one with the wings of a British jet engine (AN 1015) in it.
- Hunter Adam gun package rigged with vibration test and training gun.
- Static aircraft exhibit showing planes dating from 1917 and ranging on up through World War I and World War II by perfect research results and present day results.
- Comet, "pocket-size" bomber named by the first diamond civil engineers and powered by two turbojets.
- A display of precision formation aerobics, including five types of four Hunter and four Victor, a high and a low speed fighter, Britain's only straight and level supersonic prototype, the English Electric P1 and Hawk, the top the day off and end with Britain's beginning a second flight in a few hours.

The P1 prototype, which, several high and low speed passes over the field,

also return carrying up to 31 smaller payloads.

- A large balloon rig with a scale model Javelin and its front-line fighter tests.
- A size "nose" shows on target.
- A shock wave and supersonic flow-flight models plus their latest results.
- Guided missile test vehicles, including various systems, replicated risk of components.
- Titanium alloy with a maximum tensile strength of 77 tons per square inch.
- Hydrodynamic tests used in solar energy test program.
- Three full-scale water tanks for pressurized engine testing, including one with the wings of a British jet engine (AN 1015) in it.
- Hunter Adam gun package rigged with vibration test and training gun.
- Static aircraft exhibit showing planes dating from 1917 and ranging on up through World War I and World War II by perfect research results and present day results.
- Comet, "pocket-size" bomber named by the first diamond civil engineers and powered by two turbojets.
- A display of precision formation aerobics, including five types of four Hunter and four Victor, a high and a low speed fighter, Britain's only straight and level supersonic prototype, the English Electric P1 and Hawk, the top the day off and end with Britain's beginning a second flight in a few hours.

The P1 prototype, which, several high and low speed passes over the field,

also return carrying up to 31 smaller payloads.

The P1 prototype, which, several high and low speed passes over the field,

also return carrying up to 31 smaller payloads.



GANTRY CRANE works through hatch in top of Short Sparrow hangar to load 20,000-lb loads into high-altitude testbed's bay.

Air Research

showing exceptional accuracy stability at high speed. The wings, with tip airfoils, were shaped very much like those of the Short SR-5 research plane and seemed to have the extreme sweepback (60 degrees) of that aerodynamic predecessor of the P1.

Gloster's controversial Javelin all-weather fighter demonstrated its sensitive abilities and high-speed maneuverability.

Static Exhibits

Highlights of the static show, as were ones hidden by precise hangars, included:

- **Knowledge engine.** A single ramjet, supported on a spider web, was fired at by a Mach One bullet. Enlarging the formation of drag graphically indicated position of jet impact on supersonic flowfield.
- **High-altitude flight.** An experimental full-power test for prolonged operation above 40,000 ft without turbojet power was shown for the first time. Power cubes (before or sometime) could result in loss of aircraft through inefficient fuel at a discount to below 10,000 ft, become necessary on a long mission. New silver flexible test kit a semi-circular bowl-type, vent, and was shown, developed by USAF special pressure test, with automatic vents.

Also shown was an individual pressure capsule built during the War for Prince Marston Churchill's York, and B-11 flight, complete with internal telephone system, to provide equivalent



GEN PACK with conversion case is ready to be started into Marston Marston belly.



ADEN 38-AM, CANON is standard around the Britain's new jet fighter tests.




LARGE-SCALE JAVELIN MODEL used to open hatch hangars explore balloons.

FOR EMERGENCY HYDRAULIC POWER

USE A

DEPENDABLE




Model AA-19033, Vickers Electric Motor Driven Auxiliary Hydraulic Pump for 3000 psi

VICKERS® MOTORPUMP

- ★ **PROVEN RELIABILITY**
These Motorpumps have accumulated remarkable records of dependability on numerous military aircraft and major airlines.
- ★ **HIGHER OVERALL EFFICIENCY**
Vickers Motor Pumps have 92% overall efficiency, resulting in higher motorpump overall efficiency.
- ★ **LESS WEIGHT**
High pump efficiency and low starting torque permit use of a smaller, lighter electric motor. Total weight of Model AA-19033 is only 33 1/2 lb., including radio noise suppressor (3.4 lb.). Hydraulic pump weighs only 2.18 lb.
- ★ **EXPLOSION PROOF**
Conforms to Specification MIL-M-8829.
- ★ **LOWER POWER DEMAND**
The more efficient pump means less current drawn - longer emergency operation.
- ★ **DIRECT DRIVE - NO GEARING**
Ability of pump to operate at high speed permits direct drive at 7350 rpm.
- ★ **LOW STARTING TORQUE**
Less than 10% over maximum running torque.
- ★ **SMALLER SIZE**
Higher overall efficiency, low starting torque, and high pump speed save space as well as weight.

For more information about Vickers Motorpumps, ask for new Bulletin A-5207.



Performance curves of Vickers Motor Pump Model AA-19033

VICKERS Incorporated

1462 SAKRAH BLVD. • JETPORT 32, MIAMI, Florida
 Division of Dresser Industries, Inc.
 Opa-locka, California, 91615 • (408) 444-4444
 Arlington, Texas 76010 • (817) 444-4444
 Detroit 26, Michigan 48206 • (313) 444-4444
 Additional Service Facilities at:
 Miami Springs, Florida 33166 • San Diego 92161 • (619) 444-4444

REPRESENTATIVE: VICKERS INC. • (212) 671-1111 • (212) 671-1111 • (212) 671-1111



38 HESON WING spares undergo static test in Fairbrough - installed on

of less than 8,000 lb. up to 25,000 lb. it was never used in practice.

- **All-weather operation.** Since aircraft flies over snows of mountainous terrain, operators with Motor-Pumps automatic safety at altitudes between 40,000 and 50,000 ft., from English Electric Canberra. An actual test was also shown with the following design and safety parachute. The 10 ft. test in real test installed in production aircraft.
- **Parachute development.** Various types of test up to 4,000 lb. in weight were shown, including from Fairchild C-119 which has been in use for several years to the Ministry of Supply for each experiment. Many types of chute were installed including a single 60 ft. diameter parachute type for the heaviest load. Metal pulley or platform for loading gear on vehicle for dropping was also shown in static.

Usual application of tests particularly in experimental tests 7078, low-speed research tests, was small enough in right wing top for applying known same constant. This machine, also had 1,000 lb. sand-filled loads under the same wing, also load in the leading edge, for known lifting moment. The other wing was obviously loaded with a single center and tube to make a full cable.

- **Controlled engine development.** No operational engine were displayed, but a large number of RTVs (Rocket Test Vehicle), CTVs (Compass Test Vehicle), ATVs (Aircraft Test Vehicle), and GTVs (General Purpose Vehicle) were on view. Together with guidance components and systems. One large result, the RTV-3 was shown after having been recovered from the sea, following test firing, with its fuel

We fly the far North



Our flights extend to Labrador and Alaska... wilderness country where landing fields are far apart and services facilities remote. That's why we must demand the most reliable engine performance possible.

Recently, we performance-tested the quality of your engine overhauls against those we had been using. The Airwork engines performed perfectly.

Now, we've switched to Airwork for dependable performance and to your Exchange Program for increased economy.

Charles Sharp

Supervisor of Flight Operations, Great Lakes Carbon

AC spark plugs are now distributed by Airwork.

ARLINGTON



ATLANTA

MIAMI

NEWARK

Airwork

CORPORATION
 Millville, New Jersey



AEROBATHMIC 'GLOVE' on Vickers, turbo provides flight data on new wing design


AVIATION WEEK, August 8, 1955

ENGINEERS AND BUILDERS OF OIL HYDRAULIC EQUIPMENT SINCE 1921

New High Performance Fastener

EXCEEDS ULTIMATE TENSILE and SHEAR LOADS OF NAS 547

New PANELOC High Performance Aircraft Fastener Carries Primary Structural Loads in Shear and Tension with Minimum Deflection and Minimum Sheet Separation.



Assuring high strength, quick release, rotary type fastener for advanced aircraft designs. Available in standard and curvature adaptable types, in sizes 1 & 2 with full float as specified by NAS 547. Spins and clamps with quarter turn, stud ejection shows unlocked condition. Laminé pressure sealed. Adjustable for sheet pack up in accordance with NAS 547, thus simplifying stud assembly. Catalog and price list belong in your file. Send request today.

PANELOC Formosa and versatile line of self-drill, self-aligning, high performance fasteners. Sizes 1, 2 & 3. Panel Fasteners, Rotary Lockers and Snap Fasteners.



Fill in Coupon or Write Letter for Catalogs



PANELOC

Send: ☐ Name ☐ Title

Company

Address

City

State

Zip

Phone

Telex

Radio

of basic and recovery purchases.

Many film exposures were shown including several from the movie that is being launched. Most graphs show a factor of double-wing control surfaces, which eventually broke off, resulting in even greater stability of the aircraft.

• **Armament.** The aircrafts, powered 30 mm. Aden cannons, showed weapons on combat aircraft fighters, were displayed. A compact, short-barreled cannon, the Aden has a cyclic rate of fire of about 1,000 rpm, and a muzzle velocity somewhat under 1,000 ft/sec. Most current fighters carry eight to ten seconds worth of ammunition. Gun barrels are good for over 5,000 rounds. A demonstration of Hunter training was a memorable gun pack, was a feature of the static pack display.

Also shown were five British rocket pods, not yet installed. One, labeled "rocket launcher, this, again," and weighing 114 lb, had seven barrels with external spin rate.

More experimental in appearance was the 60 mm rocket battery, for a wing tip installation, with stabilizing fins and containing 31 rounds. These new British AAMs were also exhibited with other types of testing for stabilization. A smaller battery contained seven 60 mm. rockets. For ground attack, the new ML 12 underwing rocket launcher was shown, with dual-staked 1 in. No. 1 NA. 5 projectiles, the "hunter aircraft."

• **Bombs.** Close attention is obviously still being paid to conventional bombs, despite atomic examples. New series of precision bombs, with 30-in. fin, ranged from 500 to 5,000 lb. In the static pack, loading of a 10,000 lb. missile as prototype. Short Spenser was thought to be a guide to Vindicator technique. Loading involves gunner's fuselage, with first going through launch to upper deck, and lifting bomb from truck under the bomb bay.

Aerodynamics Research

Another major section of the display was devoted to aerodynamic research. Of particular interest was a free-flight testing system from a large late balloon, of large-scale models in an extension of research in a vertical wind tunnel. The example shown suspended beneath the tethered balloon was a dynamically similar model of the Glanier Jumbo disc. After ascending to about 3,500 ft. beneath the balloon, the model is released in the direction of the desired spin, and then released with its controls set at full roll, full up elevator and neutral aileron.

After four turns of the spin, a program timer applies corrective control—full opposite roll and aileron then full down elevator—and holds it for five seconds. Recovery follows in less than 1 second, and the controls



Now...join me aboard the

VISCOUNT

world's first turbo-prop airliner

Enjoy faster, quieter, vibration-free service between the following cities.

CHICAGO • PITTSBURGH • WASHINGTON • NORFOLK



Powered by  ROLLS-ROYCE


Manufactured by  ROLLS-ROYCE

For Viscount reservations call Capital Airlines or your Travel Agent

Capital

AIRLINES

when **ADVANCE**
supplies your relays...
you get **ACTION**



Action in Squad's Home. Chosen from a wide variety of in-stock relays, available for immediate shipment from Burbank or Chicago. Lightweight, small and precision built, **ADVANCE** relays stand up under rugged service. They're specified by major manufacturers the country over.

Relay as "Specialist." When you need a specially designed relay, ADVANCE will work closely with your engineers to determine accurately what's needed...develop it in a minimum time. You'll find us ready to cooperate with you on any relay problem.

Action on Producing Belays. There's manpower here to build your belays right on time, and at the lowest price consistent with top quality. It's our aim to help keep your production rolling — your products operating dependably. What ever your relay problems...call ADVANCE for action.



ADVANCE ELECTRIC AND RELAY COMPANY
2405 NORTH HADAM STREET, BURBANK, CALIFORNIA
AN ELMER NATIONAL SWITCH COMPANY AFFILIATE

tensile high strength in the 720 °F temperature region, expected in steel temperatures at the higher Mach numbers. The tensile strength of these alloys is so high as 97 ksi owing to, twice that of the aluminum alloys. Their advantage over the alternative stainless steels is that they are some what stronger for only half the weight.

While the importance of the various group of high transmittance materials is fully realized in Britain, most of the research has been directed not to reduce, and other national research centres in Germany. Very little work has shown at Tinsborough. Other important developments in the metallurgical field are non processes, to cut the cost of titanium sponge and powder. There are schematic diagrams of a possible process using chlorides for the reduction of titanium oxides. The process involves the use of a molten salt bath and charged from a solid phase, metal oxides. The other schemes were illustrated for titanium in a different way.

Hinting Problems

One of the problems of knowledge learning is equivalence space in the term perceptive gradient in the space with structure of the wing. The difficulty in assessing the stress pattern developed arises from the fact that until recently it was extremely difficult to simulate the nature of the thermal loading on a wing model, since the condition is a transient one and is consequently a function of time. The main requirement was for a heat source on the model which could be accurately de-


NTS3 for B-III XH-40

A 425-hp, free-piston gas turbine designed and built by Lycoming Division of Veeco Manufacturing Corp., will power the new lightweight A11-40 utility engine being developed for the U. S. Army (ENR July 17, p. 7).

First details of Examine's new XL33 model it is designed for "workhorse" applications in fixed-wing aircraft as well as rotary-wing types. The engine features a horizontal drive, although it is used applications, seaward or installation. Horizontal power extraction can be made, Examine reports. Contact information and price is \$750,000.

Development of the XT55 has been under direction of Dr. Nathan Fenn, Lexington, vice president-technical engineering who was vice president-engine development for Judd in Germany during World War II where he worked on the Jumo 200 engine. The XT55 is one of two turbine engines being developed for Air Force at the company's Stratford, Conn., plant.

TONS OF POWER



...And Sargent possesses aircraft controls make that money instantly available at the touch of a finger.

The design and manufacture of pressure equipment has been the specialty of Sargent Engineering Corporation for more than 30 years. For 30 years Sargent has been providing pressures, airtight control units—by design, pressure, and mechanical—in the country's leading oilfield manufacturers.

We have the "know-how" to help you solve your most difficult control problems. Write today for your copy of the NEW illustrated story of Sargent's organization, methods, and manufacturing facilities.

Handbook of Excellence

Page 4890

ENGINEERING CORPORATION
2535 EAST 90TH STREET
HUNTINGTON PARK, CALIF.

¹¹“Good will” is the disposition of the pleased customer to return to the place where he has been well treated.

Cornelius

"PACKAGED"

PNEUMATIC SYSTEM

SAVES WEIGHT and SPACE



The Cornelius Compressor, Model 130, 25CFM, 3000 PSI, is used in the McDonnell F3H-2 and F3H-1, North American F2-4, F2-5 and F3-4, Grumman F4U-7, F4U-8, Grumman F6F-4, also on order for the Lockheed P2V, Grumman S2F and Martin P3M. Thousands of private buyers order all equipment confidence is proof of outstanding performance.

The Cornelius Model 130 compressor is the heart of the complete Cornelius "packaged" pneumatic system which includes inlet air filter, starting relay, radio noise filter, moisture separator with automatic condensate dump and heating element, back pressure valve, check valve, relief valve and pressure switch.

Compact Design, Saves Space—Entire air supply system occupies only slightly more space than compressor alone in conventional system.

Weight Savings of 5 pounds or more are possible by eliminating separate system components, associated tubing, fittings and flow connections.

System Leakage is Reduced to a minimum because integration of components removes possible leakage sources such as flare connections and O-ring sealed fittings.

System Reliability is Assured because each integral component is designed specifically to give optimum performance in combination with the other components.

Time Saved by installation and servicing of one unit is another valuable benefit which only Cornelius "packaged" pneumatic systems offer.

The Cornelius "packaged" pneumatic systems are available with either DC, AC or hydro-pneumatic motor drive. Please write us in order that a Sales Engineer may discuss with you the application of this "packaged" system as well as the many other pneumatic components which we manufacture.

THE CORNELIUS COMPANY 550 - 38th Ave. N. E., Minneapolis 21, Minnesota

PIONEERS IN THE DEVELOPMENT OF AIRCRAFT PNEUMATIC SYSTEMS

ated and measured.

This requirement was satisfied in the development of the Phipps quartz tubular air-end heating element. These tubes, only 1" in diameter by 14" long have an output of up to 3 kw. each. For measuring the actual collection time, Farnborough has developed a sensor using a fluorescent lead in the working element. The characteristics of the sensor conductors are such that its resistance drops from 2000 to 600 ohms when the current increases from 0 to 1 watt/cm². The sensor has a delay of less than 1 sec. An electronic control completes the rig as developed at Farnborough. Into it are fed the theoretical atmospheric conditions. In gilder with the last output is measured by the pressure.

The computer adjusts the heat input to equal the theoretical aerodynamic heating data fed in at the other end of the computer. The thermal zones are then measured with conventional strain gages. A model of a structural testing frame with three heating air nozzles disposed over the wing skin is a Mach 3 aircraft suggested the shape of things to come in rig testing.

The RAL's "crash-test" rig rig through one of the largest in Europe is now too small on local dimensions to handle today's larger aircraft wings. A new structure has been designed which will not be so compromised by wing geometry. A model of this future rig showed a solid, thick, and solid wing rig for both mechanical and thermal stress studies.

A number of special techniques used in experimental thermal stress analysis were also demonstrated. Apart from the more familiar photoelastic methods using plastic scale models, the bottle-necking technique developed at Farnborough was demonstrated. With this

Pilot Stutter

Stuttering may be easier to understand than actual speech while flying. He was known as a UNAP project at Ohio State University report that a radio can get, transmitted when some airman is in high, comes through better if the speaker says "back-out, left two" rather than "yes, yes."

The "bottle-neck" system, in which the throat is constricted, is reported, proved most effective in these tests recently, one checked no person from Japan. Radio jockey and Stutterer as well as an American.

Further research will be done to determine the intelligibility of "double bottle-neck" stuttering in speech communication.



and Now!
WINGS TO GO ANYWHERE

**RUNWAYS,
SAND, SNOW,
WATER OR ICE,
FLOWED FIELD
OR COW PASTURE**

We Lead with Big Engines
Where even little ones Can't Go

Stroukoff
Aircraft Corporation
WELD TOWNSHIRE NEW JERSEY

**Famous
LOCKHEED
T-33
Jet Trainers**



Oct 11-12
Rocky Mts. Area
Michael Bred
Bedding 2 in 10 Areas

Partial installation of K&N Conical Breathers in West
Lubbock T-33 Jet Trainer

The Lockheed T-33 is the only U. S. two-place jet trainer supplied to the U. S. Air Force, Navy, and Marine Corps, as well as the air forces of six foreign countries.

For top electric circuit performance, Lockheed uses Klixon Breakers in the T-33 trainer as well as other Lockheed aircraft. The reason — Klixon Breakers are unexcelled for safe, reliable protection against short or dangerous overloads.

Like those precision-marketing plans, Klixon Circuit Breakers are designed and built to give outstanding performance under all flying conditions. They are precision cutthroats and individually scored for ultimate grip and 200% load tripping characteristics. Write for data giving concrete details.

KLIXON
METALS & CONTROLS CORPORATION

KLIXON
METALS & CONTROLS CORPORATION
SPRING THERMOSTAT DIVISION
P.O. BOX 10000, CHICAGO, ILL. 60680

system, the surface stress distribution on an actual component or structure can be visualized and determined. Some of the equipment for applying the bottle coating was displayed together with that for measuring the performance of the coating.

Another major problem concerning the structural department is that investigation of better and other educational problems arising either in the structure or the propulsive mechanism is the air or on the ground. Equipment and techniques for creating these disturbances were then:

But engine manufacturers have been reluctant to put a limit on the amount of noise emitted from cars. For each 1,000 lb. of thrust produced by their engines,

The military services are told, in a new directive signed by Frank D. Nye, Acting Assistant Secretary of Defense for Acquisition Engineering, that they are responsible for ensuring that observat-


Except where performance would be considered such turbojet engines shall consume for its construction, on 1 gram weight basis, not more than 15 lb of cobalt, 65 lb of nickel, 150 lb of chromium, 35 lb of molybdenum, 25 lb of ruthenium, and +6 lb of silicon, for each 1,000 lb of sea level static thrust delivered by the engine.

The instruction says the conservator effect should not result in reduced performance but still aim to prevent needless use of external resources or new capacity.

Starting as soon as possible in the history of a new region, a count will be made of the amount of rice available used for each 1,000 lb. of thrust and steps taken to see that it is used to confound with the other.

The armed forces are ordered by NASA to report by September 14 with cost, thrust requirements for each production and development engine model, get 1,000 lb of thrust, the gross-to-net ratio and the total thrust of each model.

Avian Inc., Woodhoad N.Y., an soft instrumental and control systems maker, has sold 99,800 shares of its Class A stock to the public at an offering price of \$5 per share. The firm is expected to declare 7.1-cents-per-share quarterly dividend on these shares in the third quarter of this year. With the offering, Avian acquired all stock in Control Laboratories, Inc., N.Y., and Avian Service Corp., Calver City, Md., formerly affiliates.

[illegible]

It's good news for car owners that the rubber parts that used to crack, chip, and practically disintegrate under tough road and weather conditions are being replaced with parts made from super-durable Enjay Butyl. In over 100 vital places, Enjay Butyl helps give many '85 models the performance and appearance that make them a pleasure to drive, an economical unit to maintain.

If you make a product in which rubber is used, or could be used, you owe it to efficient business practice to investigate the many advantages that Eriyl Batyl has over other types of rubber. Its price is a definite advantage, too. Complete laboratory and technical facilities are at your service. For full information contact the Eriyl Company today.



ENJOY COMPANY, INC.
12 West 51st Street, New York 19, N.Y.
District Office: 11 South Portage Park,
Akron 3, Ohio



The super-durable Rubber with outstanding resistance to aging • abrasion • heat • chipping • cracking • ozone and rotting • chemicals • acids • heat • cold • sunlight • moisture

35 SUCCESSFUL YEARS OF LEADERSHIP IN SERVING INDUSTRY



For American Electric Company's electrical equipment, General Electric's improved electric system on this and other Pan American Boeing planes plays important part in passenger comfort, and confidence in service.

HOW PAN AMERICAN IMPROVES AIRCRAFT



Located in nose of Boeing 707, G-E electric panel helps assure electric system reliability.



Arrangement of G-E circuit breakers shows high reliability—important part of Pan American's program for under maintenance of electric systems.



At Pan American's service shops, G-E field engineer aids in helping to improve reliability of electric components.

Long life of G-E aircraft generators has been a benefit through improved check readings and loadings.

The new Douglas Super 7 G-E power makes maiden voyage for Pan American's 18,000-hp trans-Atlantic winging, representing 100 million miles of flight. Aircraft's tests with G-E electric system led to Pan American's specifying G-E for new fleet of "Super 7s."



ELECTRIC SYSTEM RELIABILITY

G-E design engineering combined with first class field service help Pan American increase life of power generating systems.

Dependability of Pan American World Airways' aircraft generating systems is the result of a continuous co-operative effort between General Electric and the airline to increase the life and reliable operation of the G-E components which help make up the system.

The reliability is essential for Pan American's flights travel over jungle, desert, ocean, and rugged mountain terrain in all parts of the world. Any trouble encountered in the plane's electric system could cause time-consuming delays at remote air fields. These could be costly to the airline and passengers.

G-E develops preventive system

To meet such problems before they occurred, Pan American called on General Electric to work closely with them and the airline manufacturers. Conferences were held, and G-E application engineers designed and demonstrated a general-purpose system which fulfilled all the requirements. So successful was this system that adapta-

tions were installed on Pan American's new DC-6Bs and DC-7Bs aircraft.

At the same time these engineering studies were being made, G-E placed on a continuous field service to assist Pan American's service shops in improving the component performance of the system. This field service assistance with the airline is still operating today. The result—the G-E electric system has given Pan American the increased safety protection its service demands, as well as better operating performance. That's why they are specifying G-E generator systems on new aircraft purchases.

Service available to you

G-E application and field service engineers can help solve your electric system requirements regardless of where you are located. For further information, contact your G-E Aircraft Specialist through your nearest G-E Apparatus Sales representative today. General Electric Company, Subsidiary S, M, Y. 404

Progress Is Our Most Important Product

GENERAL  ELECTRIC

This G-E rocket team is developing a wide range of reliable, high performance engines

On the right, lined up on a rocket test stand, are 34 members of General Electric's rocket development team. As representatives of the Company's Aircraft Gas Turbine Development Department, they offer four reasons why G-E has the capability to develop reliable, high performance rocket engine systems, sub-assemblies, and components of all types.

REASON NO. 1—AVERAGE OF EIGHT YEARS' EXPERIENCE PER MAN. All told, this group has over 250 years of experience in high Mach powerplants. This cumulative know-how, as vital in aircraft powerplant work, is ensuring faster, more efficient rocket development activity at General Electric.

REASON NO. 2—PROVED ABILITY. Those same men actually helped to generate modern U.S. rocket engine activity, took part in over 87 German V-2 test flights after WW II. They have designed jet-turbo, liquid-solid, solid and nozzle propulsion systems. They provided the

engine for the first large rocket in the Western Hemisphere, developed another with one of the highest specific impulses ever achieved.

REASON NO. 3—ADVANCED NEW FACILITIES ARE NOW AT THEIR DISPOSAL. General Electric is carrying on a \$100 million research and development program on combustors, materials, and components of powerplants for aircraft and missiles. And the rocket engine staff now has access to development facilities such as the AGT Motor's Laboratory and the AGT Component Development Laboratory at Cincinnati.

REASON NO. 4—FIRM SUPPORT OF GENERAL ELECTRIC ORGANIZATION. The entire G-E Aircraft Gas Turbine Division with its production capability and G-E's nationwide defense sales and service chain now support the design and development of G-E rocket engines. Add up the total. If you would like further information, contact a G-E Aircraft Specialist via your nearest G-E Apparatus Sales Office.

Progress Is Our Most Important Product

GENERAL ELECTRIC



Advanced rocket engine undergoes test at U.S. Army's Mifflin Test Station. The first large rocket static test station in the U.S., Mifflin has highly sensitive facilities. Complete instrumentation gives G-E engineers accurate information on engine performance in static tests.



"Consulting our jet and rocket engine design, development, and production capabilities within AGT is allowing us to make rapid strides in the rocket field," according to Vice President C. W. LePrieux, shown here (left) with G-E President R. J. Condit.



Over eight years' average experience is the mark of these G-E propulsion engineers, shown here at the Mifflin, Pa., Rocket Test Station. 1. J. C. Jenkins, 2. H. M. Slater, 3. B. Davidson, 4. F. E. Schulte, 5. E. H. Hall, 6. D. Carlson, Manager, Aircraft Gas Turbine Development Department, 7. T. S. Tinsley, 8. H. C. Adams, 9. P. L. Dunlop, 10. J. H. Bowers, 11. J. F. Whitlock, 12. W. S. Kirsch, 13. P. J. Wilson, 14. J. Amadio, 15. G. E. Simmons, 16. P. Gray, 17. R. W. Lyons, 18. J. A. Giff, 19. A. J. Gorman, 20. S. J. Kowalski, 21. O. C. McPherson, 22. B. J. Bonadire, 23. C. E. Bush, 24. L. Cherry, 25. C. P. Brachman, 26. R. B. Johnson, 27. R. E. Bell, 28. C. G. Doble, 29. R. W. Brachman, 30. J. M. Krize, 31. S. E. Pralock, 32. E. O. Shotton, 33. G. H. Morone, 34. E. J. Fager.

In testing,
In development,
In performance...

Engineering counts AT CANADAIR

Canadair has a new Engineering Test and Development Laboratory... this addition to Canadair's facilities opens the door to the broader, more intricate phases of development work which concern an engineering demands.

Canadair engineers have never hesitated to break new ground in their constant search for scientific advancement and are presently engaged in solving the complex problems associated with the development of guided missiles and long-range spin-sustaining aircraft for the RCAF.

Typical of its engineering performance record is Canadair's 7800 program which has involved the production of six different versions of the aircraft without interruption to scheduled delivery. Yes, engineering counts at Canadair... another reason why people who know say "you can count on Canadair."



CANADAIR

— AIRCRAFT AND MISSILES —
LIMITED, MONTREAL, CANADA

A subsidiary of GENERAL DYNAMICS CORPORATION, New York, N.Y. — Washington, D.C.

204-1072

pal Airport, W. Va., for a new 65,000 sq. ft. plant to house aircraft modification, assembly, painting, sheet metal work, and other fabrication in addition to administration and engineering. Facility is expected to be completed early next year.

► New address: H. E. B. Machine Tools, Inc., has moved its executive and sales offices from New York City to large quarters at 788 Clare St., Longwood, N.Y. Stoughton Corp., Dana, Pa., order of insulated thermosetting plastic, has moved to Rochester, N.Y., sales office to 157 W. Commercial St., East Rochester, N.Y.

► Fusion Roller Bearing Co., Canton, Ohio, has completed \$500,000 for further expansion of its factory plant, bringing total expenditure to building up facilities to more than \$10 million. Rollup program is expected to be completed by the end of next year.

► Harboring Steel Corp. and Precision Castings Co. has merged. With the new organization Harboring's operations will cover 31 plants and sales volume is expected to double to about \$60 million.

► Extruded deck roofing panels which comply in size to ducts, but from extruded blocks of reinforced plastic are produced at the Hulschke Chemical plant of Kays Aluminum & Chemical Corp., Oakland 33, Calif.

► Production testing problem was solved by Stoughton Machine Tool Co.'s Division Two, Rochester, N.Y., by use of specially designed R700 in double base made of Inconel-type steel instead of conventional alloy materials. Letter tested under agreement test conditions which include hydrostatic shock at 750,000 P. Compression constant R700 is manufactured by Russell's Corp., 29 Princeton St., Berkeley, N.J.

► Pacific, Inc., Skokie, Ill., has formed a new Instrument Services Division to handle consulting and installation in the instrumentation and automation fields.

► Sales and service branch office of Cleveland Precision Tool Company has been established at 1000 Hempstead Turnpike, Levittown, N.Y., under the direction of T. J. Baker.

► New York Air Brake Co. has appointed American Electric Ltd. Montreal and Montreal Air Engine Ltd., Winnipeg, Canada representatives for Stoughton aircraft hydraulic pumps manufactured in the company's Watrous, Ia. plant.

Ex-Cell-O Precision at Production Prices



FUEL CONTROL AND
METERING ASSEMBLIES



HYDRAULIC & PNEUMATIC
ACTUATOR ASSEMBLIES



FUEL NOZZLES FOR
JET ENGINES



JET ENGINE BLADES



MISCELLANEOUS AIRCRAFT AND
COMMERCIAL PRECISION PARTS



JET COMPRESSOR ROTORS

Ex-Cell-O's facilities include laboratory control of materials, design and process engineering, machining of all materials, complete quality control to meet the most rigid specifications, and delivery to meet customer requirements.

For information or a quotation, write or phone the Precision Products Division of Ex-Cell-O.

EX-CELL-O CORPORATION • DETROIT 32, MICHIGAN

MANUFACTURERS OF PRECISION MACHINING TOOLS • PRECISION SPRINGS • SPRING TIEES • AIRCRAFT AND LAND VEHICLES • DIECASTING MACHINES • AIRCRAFT AND COMMERCIAL PRECISION PARTS • SHOT EQUIPMENT

HERE'S HOW YOU CAN TELL



The KEYSTONE 5-POSITION INDICATOR at present is being used on aircraft to report more than 60 operating situations. Simple, easy to read, hermatically sealed, reliable, it will report any variable that can actuate a switch mechanism.

Conforms to spec. MIL-I-6839,
Landing Gear Position Indicator.
Send coupon for complete infor-
mation.

**KEYSTONE WATCH CASE
& INSTRUMENT DIV.**
THE RIVERSIDE METAL COMPANY
RIVERSIDE, N. J.

Please apply late, and immediately on 3
nonconsecutive Saturdays from 10:00 a.m. to 1:00 p.m.

In _____
 Name _____
 Phone _____
 Address _____
 City _____ State _____

LETTERS

More on Lights

As a working artist, poet, who has given a lot of time during the last five years to studying problems associated with racial equality feelings, I have followed the news items in your magazine, dealing with the "Wages, some Catholics and Ben" controversy, with great interest.

However, the letter written by Mr. Guy Fournier under the heading "Pro-Sinclair Lights" published in some issue of June 1936 appears to me to contain so many inaccuracies—and not a few misquotations directed against professional online photographers in the interests of truth and justice, but compelled to take the liberty

and a more gradual growth in "muscle mass" and a marked bias toward the vestibular and basilar portions of the cochlea, were indicated in large numbers of single oval windows in kidneys of the sick mice, which I have had subjected to experimental infection, at which various points considered to be the best values that I have had no experimental experience in had verified of the ligature modifications.

I have, however, on an several examinations of similar glands of uninfected animals, where we had, arranged to be done in experimental criteria to see what the pilot water, from an approach light system. The divisions are both have always been attributed to such as lesions of the vestibular and bas-

It would seem that Mr Peters is not fully understanding Mr Cairns when in the second paragraph of his letter, he talks with serenity, according during speeches made on consilience and his nation. To do even a small courtesy to Mr Cairns should perhaps be, and "There has been no moderate writing from M15

INTERPRETATION OF GUIDANCE
GIVEN TO THE PILOT BY THE APPROACH LIGHT SYSTEM showing an approach made on the centerline, and later on 11 to assist center during the approach due to a rapid or structural failure. It serves a light center to blind, thus on the approach light system. It is not suitable to comment on the accident referred to as Newark on Oct. 30, 1971. I believe the accident here caused by centerline and the centerline in Europe is still valid.

In the paragraph under the sub-heading "Pilot Skills," Mr. Pearson (who I believe is not a practicing airline pilot) makes some very dangerous assumptions with which I submit the members of the profession would agree.

A pilot study has to be treated with care. Lengthy and expensive means of data collection may be kept in training, but only in the exercise, one of his skill and knowledge but also be spread in several "behavioral" and "management" training. However, Chelid, that also is a more expensive than the other, value more than the cost and the cost because no previous training is needed to interpret its results. This is because the system is based on the "behavior" of the same student, which are used during normal operations in good conditions. In contrast, as time as a pilot can measure in right way.

than be in a case (which is something of an *ad hoc* rule, pilots are trained to do from initial release, when an first burst is weak), he cannot go along on the system. The visual information provided to the pilot on both angle and undershoot, and therefore SAFE. Can Mr. Tarnoff seriously suggest that we should then say these advantages and some other reasons operate turning on an "assumed return" and then conclude that when the constant pressure is needed to keep on the threshold? (This is a possible finding of the FAA on constant pressure of the pilot's eyes on the threshold.) The pilot not only needs continuous audio turning but also constant practice to maintain his skill.)

"Effect" (Carré). In his paragraphs under this sub-heading, I confess I am unable to follow Mr. Parsons' reasoning. He says that he is not moving up a platform that shall stand side by side with other such common-sense men. The first I think, is called by Mr. Parsons "To Defeat," but in plots it is the line of approach to the subject in the textbook approach light (table). The second I think, is referred to by Mr. Parsons as "The Salt of the Earth," and refers to the segment of the approach light system, control, by the plate, as he descends the platform. The height of this segment is defined as its forward limit by the third stand range and it is the

These coastal ranges are extremely hard to traverse under operational conditions (especially under those of shallow cultivation) and because of this a lot of agriculturalists have taken both as to the importance of the dense coastal range, and as to the effect of encroachment on the land. Landmark surveys are in use in Europe, at some airports, too, data

terms of Minimum Visual Range (not to be confused with Meteorological Visibility) and for many operations on, of the order of 100 yards. Landing in a fog or dense rain means a runway approach light system of the omnibeam and bar type. The pilot has a clear (and range) when over the lights of some 1,000 to 4,000 feet. Under these conditions, with a cockpit cut off at some 12 degrees, a figure attained by almost every commercial airline (after which is the approach procedure), the pilot will, even a small

Carder-Park Approaches" In his last paragraph, I feel that Mr. Pearson is being unfair in his use of American pilot language. Such he is sure that U. S. negotiations will result in being together rather

man. Worth welcomes the special for readers on the issue in the magazine's editorial address letters to the Editor, on Week, 130 W. 42 St., New York, N. Y. Try to keep letters 500 words and give a general opinion. We will not print anonymous letters, but names of writers will be withheld on request.

new Boeing jet tanker
to stretch America's Air Arm
with mid-air refuelling

Almost daily, continuous flights halfway around the World are being made because huge KC-107 tankers meet bombers for refueling in mid-air. Tankers like the Boeing

Newsier will produce the address for the HQ-420 address, but you must provide a valid e-mail address.



Please mail us 100 copies of your new manuscript to:

Age	Title
Company
Street
City	State





NUCLEAR PROPULSION ADVANCED DESIGN

WHAT INTERESTS YOU?

Lockheed's Georgia Division long range expansion program requires engineers in all categories. Qualified engineers interested in the complex and exciting developments ahead in a progressive Engineering Organization are invited to inquire, in strictest confidence, for more information.

LOCKHEED
ENGINEERING PROFESSIONAL PLACEMENT
LOCKHEED
AERONAUTICAL CORPORATION DEPT. AV-100
261 HANGTRY RD. S. ATLANTA, GEORGIA

• LETTERS

heights are closed (see) and is osteological stability in fixed segments 400 and one, 500 and 1, 200 and 1, the last is most prominent. Operations are still held in 100 and 3. This (usually) prevents most injury plus from many attempting approaches in the lower stability, limited.

In Europe, both operation and legislation have suggested that control height is much dependent on the current characteristics of the aircraft coupled with the mass in the pressure altitude, while the stability (often) is much dependent on what the pilot can achieve. For this reason, it is now possible in terms of recent control range and NGI osteological stability and control according to the approach and current lighting system is one.

I do not think that many action pilots, who have successfully completed landings in Europe, Visual Range, a lot in 100 made a solid approach with the Pilot's decision of 10 in a "Golden Rule" approach. To make such a landing is a motionless, long, straight, smooth, and a wing loading of around 10 lbs/ft, but as an approach speed of the order of 100 mph, there is a high degree of control.

To make such a landing, often when used at the end of a long day, the pilot in the control system, an approach light system which the pilot has to see and make a decision to use.

Finally, Mr. Pearson's quote (which is interesting) that "ANY approach light system is the subject of a 'V' (Visual) Operation." In the context and for action, no doubt, but, "VFR (Visual) flight" is what it is possible to make, approaches, all relate to the end of the (real) indication from the "VFR" (V) light, back down. I see if the pilot is not in the pilot seat, still be able to see enough to see all the reason to the ramp, but at most, expects the work done, still has to be able to see enough to clear their marker to see from the airport.

Peter F. Buxton
11, Blenheim, Weymouth
Basing, London, W 1

Capt. Peter Buxton, retired British European Airways pilot, is based in Basing, W 1, 8 and Buxton for his current work, a pilot with the British Air Line Pilot Association.—Ed.

Vertical Gyo


In our July 19, 1965 publication of the article "Gyro" appeared by Capt. A. C. Buxton, the following appeared:

Readers' attention is drawn to the fact that some readers are interested in the gyro design of the gyro, but, at least, after a look in much less than 20 minutes. In that case at 200 and 10°.

It is obvious that you are not aware of the gyro design of the gyro, but, at least, after a look in much less than 20 minutes. In that case at 200 and 10°.

Thomas W. Lee
10 Carter Street
Newburgh, New York

Design News from Bridgeport Thermostat



SEAMLESS METAL BELLOWS AS SMALL AS 1/4" DIAMETER

For instrumentation, Bridgeport bellows in 1/4" and 5/64" diameter sizes offer many new opportunities to design engineers. These tiny, seamless metal bellows are typically formed of brass, phosphor bronze, beryllium copper, steel and other metals. A wide range of materials and characteristics is available.

BELLOWS ASSEMBLIES

Bridgeport specializes exclusively in metal bellows of all types and sizes, and complete bellows assemblies. Savings in time, trouble and money can be made by buying complete bellows assemblies... let Bridgeport show you how.



Robertshaw-Fulton

CONTROLS COMPANY

BRIDGEPORT THERMOSTAT DIVISION • MILFORD, CONN.

Send me the Bridgeport bellows data checked below. See P. 1408

- ☐ Full details on new, small-diameter bellows
☐ Bellows Engineering Bulletin #125 (28 pages)

NAME _____

COMPANY _____

ADDRESS _____

CITY _____ STATE _____



McDonnell F4U Corsair

Latest version of the Navy's outstanding McDonnell F4U Corsair is powered by an Allison J71 Turbo-Jet engine with high altitude characteristics. The all-weather, supercharged fighter combines atmospheric speed and fighter maneuverability with the military use of an attack bomber.

Two New Masters of the Blue

—Both Powered by Allison's 10,000-Lb.-Thrust J71 Turbo-Jet Engine



Martin XP5M SeaMaster

World's first multi-jet attack airplane, the Navy's Martin XP5M SeaMaster, is powered by four Allison J71's with afterburners. It is in the over 430 MPH class and designed to cruise steadily at 45,000 feet.

VISIT GENERAL MOTORS POWERAMA

World's Fair Celebration of the 100 Million GM Diesel Horsepower
Lake Shore—South, Chicago • August 31st through September 16th



\$75,000,000 Expansion of Allison Research and Test Facilities

To provide development facilities necessary for leadership in the aircraft engine field, General Motors now has under way a \$75,000,000 expansion in its long-range engineering program, which will give Allison the most modern gas-turbine research engine-development center in the world. This program will nearly double

the 500,000-square-foot area now devoted to engine research, and require approximately a 40% increase in engineering and technical personnel. It has as its long-range purpose the development of gas-turbine aircraft engines that will far exceed today's high standards of performance in military planes.

Special opportunity for Engineers and Technicians.
Write: Industrial Employment Section

ALLISON DIVISION OF GENERAL MOTORS, Indianapolis, Indiana



ALLISON TURBO-JET
AND TURBO-PROP ENGINES

... more than six million hours of flight time — experience where it counts most — in the air!



NIKE

Lent in Norden-Katay for:
 SYNCHRONOUS + BEING MOTORS +
 DIGITAL CONVERTERS + RATE
 GENERATORS + RESOLVERS +
 MACHINE AMPLIFIERS + GEAR
 TRAINS + POTENTIOMETERS +
 NAVIGATIONAL SYSTEMS +
 FIRE-CONTROL SYSTEMS + SERVO
 MECHANISMS + AIRBORNE
 INSTRUMENTS + ROCKET DIRECTOR
 SYSTEMS + AIR DATA INSTRUMENTS +
 COMMUNICATION EQUIPMENT +
 COMPUTERS + REGULAR CALIBRE +

RESEARCH & DEVELOPMENT ORGANIZATION:
The Molecular Laboratory, White Plains, N.Y.

MANUFACTURING DIVISION:
Farmingdale Government Division, New York, N.Y.
Cookson, Long Island, N.Y., Farmdale, California
Lawrence and System Division, Milford, Connecticut

JOINT ADVICE: Nuclear Science and Engineering
Corporation, Farmdale, N.Y.
Cookson, Long Island, N.Y., Farmdale, California



NEW MECHANIZED COMPONENT PLACEMENT machine, especially designed by General Electric for small production runs, can be manually operated but eventually will operate from punched-tape instructions. Operator moves handle (1) to position stylus (2) within its motor template (3) which positions potted circuit board (4) so placement head can install component extracted from tape magazine (5).



COMPONENTS ARE MASS-LOADED into magazines by propellant machines (left) that simultaneously trim and form their ends. Magazine cases are then manually loaded into one of 40 stations located around the periphery of the compound document machine (right).

By Philip J. Klane

The new machines are designed specifically for small production runs so characteristic of the garment industry. LINKED specifications in airborne input, navigation, communication and data transmission systems.

EMILIO's new concept place

graph and template, similar to a Windows menu punch press. However, UNED expects to have the machine operating automatically soon with some controls that will guide the process through punched tape instructions.

In addition, the Signal Company-owned Automatic Component Assembly System (ACAS), developed by GIL (AW May 2 p. 42), is slated for service evaluation here. Automatic inspection and functional test of end products, is already in use at Utes. LNEED expects to have new test procedures

LMED officials believe that such members of less capital-intensive processes, common to a wide variety of *exotic* equipment is fully justified both from the standpoint of economies and improved product quality. This is despite the small production run normally found in the consumer and military electronics industry.

The new \$18 million, 440,000 sq-ft LUMED facility, and its mechanization



SIMILAR WORK MOTION USED in the conventional Westinghouse punch press (left) which also employs pantograph-redundant system, will enable General Electric to use the same punched-tape drive control system to automate both the component placement machine and punch press. Left: model of an automated Westinghouse press, operating from punched cards, is shown in the right hand photo.



program, as the company's answer to the increased competition for military production contracts which GE and other defense firms are experiencing in the present barren market. With large development engineering staffs and facilities, firms like GE strengthen their hands, competing with the low-cost "job-type" operation with small engineering staffs and minimum investment in facilities.

In going to mechanization, LIMITED expects to cut manufacturing costs considerably and undoubtedly is able to offer the military an improved quality product, as important byproduct of such automation and automation.

Automation By Evolution

LIMITED's program is a step-by-step modernization project rather than a revolution, one element at a time right from the start in its manufacturing plant. F. F. Koenig, general manager, told Aviation Week: "Automatic inspection of assembled products, bonds and dimensional testing of completed components have been used for some time."

Prior to launching its mechanized assembly program, LIMITED made an extensive analysis of several different approaches to the problem and it was related to its own review and military electronic production needs. LIMITED's survey indicated that:

- Batch size of printed board subassemblies produced at Utah averaged 25 to 40 units per run.
- Number of components per board averaged around 47.
- Nearly 90% of the components had lead leads making them readily adaptable to mechanized assembly, i.e., carbon resistors, resistor and wire capacitors. Of the remaining 30%, half were resistant tubes.

As a result of this study, LIMITED rejected the "mix" type of machine and assembly system, popular by General Motors Automobile and United States Machinery systems (AW March 21, p. 68; May 2, p. 44). These employ a battery of machines, each of which installs a single component in a printed board. LIMITED's studies indicated that because of change over time, the "mix" system was better suited to high production items where lot sizes exceeded 100 units.

The GE-developed ACAS is designed for small production runs. However, LIMITED engineers, on the basis of experience gained in the ACAS program, and by adopting a system of modular dimensions for component locations, believed they could design a less costly machine for LIMITED's own immediate needs.

"Unimad" Auto-Assembly

GE's new "unimad" mechanism is capable of a sort of hybrid "mix" and ACAS approaches. The system consists of:

- Component preparation machine, which bonds component leads, trims them to desired length, and leads them into magazines in one operation (see sketch, p. 61). Each magazine holds 25 to 60 selected components, depending upon component size. Components are manually loaded into a fixture which is fed manually to the preparation machine.
- Component placement machine, consisting of a large horizontal drum with 40 component magazine loading stations located around its periphery (see sketch, above left). Each station is loaded manually with one to three magazines filled with components, as shown on p. 61.

A pantograph board is inserted in the machine, in a pantograph arrangement which can be positioned in an "X" and "Y" direction (see a Westinghouse press) in usually a position having a minor template relative to a stylus (see photo, p. 61). When the operator releases the stylus to the first hole in the master template, the board is positioned under the placement head to secure its first component.

When the operator pushes a button on the handle which guides the stylus, the placement head extracts a component from the magazine in the first station, inserts it into the appropriate holes in the board and clamps the leads.

The operator repositions the stylus to the next hole in the template (moving the printed board to a new position) and automatically secures a fast needle which causes the horizontal drum to rotate around one turn. The complete cycle is then repeated. With the present 40-station drum, up to 40 different components can be installed on one board. Printed boards are manually inserted in the machine but this step eventually may be mechanized.

Benefits of "unimad" are: better the component placement machine and the punch press run planned that way. This enables GE to employ the same basic punched-tape servo system to automate the pantograph movement in both the component placement machine and the punch press used to make the required holes in the printed boards. The punched-tape control system, currently under development, is expected to be the speedier than the other one developed for experimental application to a Westinghouse press (photo above right).



Meet Robert Asha, John Lawton and H. L. Newby

Westinghouse AGT supervising field service engineers. Asha has the Eastern area out of Norfolk, Lawton the Central area out of St. Louis and Newby the Western area out of Los Angeles. These men and the field service engineers working with them are important reasons why.



Field service engineering ... boosts jet engine life and reliability



Shown here is a service school conducted at the Westinghouse Avionics Gas Turbine Plant in Kansas City. Its purpose is to train military personnel in the servicing of Westinghouse engines. This activity is typical of Westinghouse service engineering. *220000*

For more information on how field service engineering contributes to aircraft performance ... turn the page

YOU CAN BE SURE...IF IT'S **Westinghouse**



Field service engineering ...boosts jet engine life and reliability



Engineering follow-through is a specialized part of Westinghouse service designed to help you get the best possible performance out of jet engines. 134 engines have had the allowable time between overhauls increased to 4000 hours and some engines have actually run 1000 hours. Further, these engines have been certified by the CAA for commercial operation.

At the core of Westinghouse engineering follow-through are the field service engineers. These men are in constant contact with engine users everywhere and feed back data concerning the product to design engineers. They concern themselves, for example, with such problems as engine stop. They consult with pilots and tell them how to get the most out of an engine. Operating personnel benefit from consulting with these men regarding practical engine analysis to improve engine performance.

This new concept of field service engineering is an extra service from Westinghouse that is designed to get the most out of Westinghouse engines and to help you bring tomorrow's aircraft... One Step Closer.

JANUARY 1968

Westinghouse field service engineers help opening personnel conduct engine check-out prior to test flight of Lockheed's F2V Neptune. Padded auxiliary turbopumps permit increased speeds and heavier loads. SPONSORED BY NORTH AMERICAN AVIATION

THE WESTINGHOUSE AVIATION FAMILY

Jet Propulsion • Airframe Systems Components • Airborne Electronics
Wind Tunnels • Airport Lighting • Ground Electronics
Aircraft Electrical Systems and Motors

YOU CAN BE **SURE**...IF IT'S
Westinghouse



ANTI-AIRCRAFT "NIKE" UTILIZES LOUD

HYDRAULIC POWER UNIT



A 3,000 DEGREE HOT BLAST OF FURIOUS SOUND...AND A ROCKET IS LAUNCHED. But before this awesome spectacle occurs, many products must play a dependable role. One of these products is the Loud hydraulic power unit which furnishes power to move the rocket to firing position from loading position.

The Loud hydraulic power unit uses 208 volts, 400 cycle, three phase power to operate 3,000 psi hydraulic system. The operating controls reside from 24 volt DC power.

Loud has now produced three hydraulic power units in impressive quantities for the "Nike" program, to ensure satisfactory standards.

H. W. LOUD MACHINE WORKS, INC.
80 EAST SECOND STREET, DEPT. 16, POMONA, CALIFORNIA

Engineering and Design
Manufacturing
Machine Tooling
Maintenance, California

Industrial Sales and Service for
Mechanical Power Plant Service Dept.
Pomona, California

By Order: Sales Engineer's Contract for
Service, Inc. (Underground), Inc.,
Pomona, CA.



as part of GE's ACAS program (AW
Sept 8, 1954, p. 42)

Output Rates

Power industries are that the
kerosene-gasoline (semi-automatic)
version of the component placement
as there will be able to yield 10 compo-
nents per minute, a rate which LIMEED
engineers hope to double when the
pneumatic control is added. This
company, with a normal component
placement rate of:

- 4 per minute relatively in typical per
second LIMEED production
- 100 per minute achieved in the
radio-TV industry
- 10 per minute, recently recorded
the maximum possible human place-
ment rate.

LIMEEDS "wetted" machine can
not match the output of an "in-line"
station like Aviatols, with perhaps 15
placement heads. However, change
over time for the GE machine is 40
seconds to run and one third that for
Aviatols. Still, manager of manufacturing
engineering at Eldec, 444 Atlantic
Way, CA.

For this reason, Start figures that the
GE system can have out a greater num-
ber of painted boards than an "in-line"
station where average lot size is around
40 or less, as it is at LIMEED. Where
lot size exceeds 100 parts per run, the
"in-line" system has a decided edge,
as shown in the chart below. In terms
of total investment, Start believes that
GE can build three of its own compo-
nent placement machines for the price
of one 34-head in-line system. The
GE machine development has been
financially backed with company funds.
GE's machine requires additional de-
sign changes on LIMEED equipment
to require that sub-assemblies be laid

LOT SIZE AND ANNUAL REQUIREMENTS DETERMINE WHICH TYPE OF MACHINE TO USE

LOT SIZE	YEARLY PRODUCTION CAPABILITY		
	IN-LINE	UNITIZED	ACAS
15	24,000	45,000	78,000
25	41,000	57,000	100,000
100	156,000	78,000	100,000
100	2,400,000	90,000	102,300

THREE DIFFERENT TYPES of mechanical
assembly stations are compared. Production
capabilities reflect differences in set up and
change-over times.



FOR MECHANIZED COMPONENT place-
ment machines, loads must be located in
standardized grid moments (holes), in con-
form with machine loadings possible with
mechanized manual placement (40).

not so that component loads are lo-
cated to standardized dimensions, ac-
cording to M. B. Johnson, manager of
engineering. LIMEED was a standard
moment of 0.1 inch for its component
location grid system, with increments
of 0.1 inch 1.2 inch for spacing between
component loads. A comparison of two
functionally identical sub-assemblies,
one using the new mechanical grid
layout, are shown in photo above.

Automatic Test Cuts Costs

LIMEED already has started to reap
significant benefits, including output cost
reduction, from its automatic inspection
and functional testing. Experts at
testing an equipment by previously used
manual means often exceeded its origi-
nal fabrication cost, Start says.

General-purpose automatic test
also largely eliminate the previous re-
quirement for building actual test
for each new equipment. Such devices
sometimes cost more than all other
manufacturing testing required, and in
the LIMEED job they totaled \$60-
100.

About a year ago, LIMEED got into
a new automatic tester, called
Superstar, developed by Colar Tele-
vision, Inc. (AW Feb 1, 1954, p. 58),
for inspection testing of the more than
100 different types of printed board
assemblies which LIMEED tests out.
The dip-switch board is placed in a
special fixture which makes electrical
contact at key points, then the CFI
tester automatically runs through a
sequence of tests (see photo p. 71).
These can include checks for con-
tact, leakage, voltage, impedance,
resistance, gain, or phase relationship.
Under the CFI Superstar finds a
fault in component outside predeter-
mined limits, it automatically prints out
a code number on a strip of paper which
indicates which component or circuit
is faulty, signals a warning buzzer, and
also generates with testing. The test
can perform up to several tests per
second, depending upon the type in-
solved. The largest sub-assemblies which

AEROODYNAMICISTS

★ Nine electronic and computer systems
are meeting an urgent demand for com-
ponents at Northrop Aircraft, Inc.,
America's first company in the retail devel-
opment, design and production of all
weather and electronic aircraft.

★ If your training and experience qualify
you for one of these challenging assignments,
please telephone or write collect

Mr. Robert Singer
Director of Engineering
Industrial Relations
Northrop Aircraft, Inc.
Northridge, California

★ Express how Los Angeles interview
will be arranged for qualified applicants

NORTHROP AIRCRAFT

INCORPORATED
NORTHROP, CALIFORNIA

Twist Wire 3 Times Faster with



ROBINSON WIRE TWISTERS

Split second whirling action
spins wires 3 engines in time
required for one by any other
method. Spins as much as 5140
per engine revolution.

3-1/2-ton-in. Power, Calumet
Twistwire Side cutting
Permanent bronze bearing
Jaws lock on wire, can't slip off.
Used throughout the world for
all aircraft assembly and main-
tenance.

9 Westmore, Wt. 12.00 \$15.00
12" Standard, Wt. 18 in \$25.00
Unconditional Guaranteed
Write for details, RAUPH C.
ROBINSON CO., Box 4948,
North Wausau, WI, U.S.A.


This advertisement appears every week

DEPEND ON

CLIFTON SIZE 10 SYNCHROS for *Consistent* HIGH ACCURACY

*Even Speed
Curve for a
typical month's
production of
transmitters.*

- Average Time: 10.000
- Average Size: 10.000
- Average Size: 10.000
- **GUARANTEED** Maximum
Size: 10.000



IMMEDIATELY AVAILABLE

For full engineering information on new
meters, receivers, resistors, differential
and control transformers and complete
line of Size 11 and 15 synchros, also
increasingly available, write or telephone
T. W. Shepp, Sales Mgr. (Telephone 4610)
Mak van 6 2161.

West Coast Sales: 1111 1/2 Street, 1908 W.
Coronado Rd., Los Angeles 44, Calif. 90024

cppe

SYNCHRO PROGRESS

LOOK TO CPPE FOR

CLIFTON PRECISION PRODUCTS CO. INC.
CLIFTON HEIGHTS PENNSYLVANIA



UNIMED type of conveyor, with a
different type component in each type
specific component placement in bands.

UNIMED tests and requires only 72
seconds for complete check-out, Start
says.

The period test record instantly
provides sources of trouble, in repair, and
for what which goes the record is re-
spected in Government inspection.

Using a single CTT tester, which
cost about \$15,000 with all accessories
required to handle a variety of different
bands, UNIMED is able to inspect
test all the bands found out in the
same time plant. This requires only
one part test, operator, with no special
technical skills. The same testing op-
eration previously required for tech-
nically trained operators and 14 test
technical personnel.

In comparing a second shift as the
CTT tester, Start says that a single
unit could handle the full output of
UNIMED's facilities, which has a ca-
pacity of 575,100 million per year.

The CTT tests has proven so ac-
cure, Start reports that out of a typical
batch of 100 bands tested, only a
couple got by the CTT unit which
later were rejected in operational tests
of the overall equipment. These fail-
ures were due to a pre-tensioner where
super glue immediately contact only
at certain points in the band.

Greater Versatility Coming

Outside as the present CTT Super-
tester is, UNIMED's engineers have
ideas for improving it. At present
when a different batch of printed an-
tist bands is to be tested, it is neces-
sary to plug another "negative adapter"
band into the CTT tester as well as
another fixture for connecting to key
points on the new printed bands. At
though this change in set-up requires
with a few seconds it has the disad-
vantage of requiring a large number of
different bands and fixtures. UNIMED
expresses intent to come up with a

**DOW CORNING
CORPORATION**

Silicone News

FOR DESIGN ENGINEERS

SUNBEAM "FRYPAN": CASE HISTORY OF AN ADVANCED DESIGN MADE PRACTICAL BY DOW CORNING SILICONES

Ingenuity design and successful use of
materials is reflected in the Sunbeam Alu-
minum Frypan. Typical, in structure and original
use, household appliances, which combine the
appeal of a look as source of essential
food with the convenience of easy, thorough
cleaning.

These vital features were made practical
through use of Dow Corning's Silicone. The
completely enclosed lead and thermocouple
wiring, for instance, is insulated with
Silicone, the Dow Corning silicone rubber.

Silicone glass drawing is also applied over
the wires to insure maximum dependability
in operating temperatures in the range
of 432 F. And the internal block to which
they are connected is a heat resistant silico-
neopolymer laminate.

Although the Frypan may be almost totally
insulated in water, the electrical connections
at the base remain dry and steady
assembly holds a permanent seal with
moisture. Silicone, however, remains and
permits, including several thousand
cycles, have proved that this glass
insulation is waterproof and even after
prolonged exposure to temperatures in
the range of 432 F.



Silicone Fluid Improves Doshpot Timing Device

The nitrogen impact timing jar developed
by Houston Oil Field Materials, Inc., pro-
vides a new approach to the problem of
locating tools around the depth of
oil wells. On impact, oil style gas shifts
and sends electric and pipe signals.
The new Houston unit eliminates wear and
loss equipment by removing all oil and
the lock inside the jar attached to the
pumped tool.

Another valuable feature of the new Houston
jar is regulated impact time. By means of a
single doshpot timing device containing
Dow Corning 200 Fluid the Houston jar
can be delayed while the jar is moved into
a new position. By varying the quantity
and viscosity of the silicone fluid, the op-
eration time may be varied down to a few seconds
to half an hour.

Silicone products most widely used are con-
fined by type of application. In the 1948 Houston
Guide to Dow Corning Silicons Products, a list
of applications ranges from a glass of
the properties and applications. With increasing
effort devoted to product improvement and
refinement such a silicone guide to this com-
plex field of engineering materials be-
comes increasingly important in design, produc-
tion and maintenance engineers.

"What's a Silicone?" is the title of a 23 page
brochure which answers that often asked question
in considerable detail. Included and illustrated,
the brochure has earned an international reputa-
tion as the most interesting and informative
account of silicone ever published. No. 47

Silastic Insulates, Protects Flexible Woven Heater Pad

Proof of the effectiveness of Silastic® epoxy
silicone is found in the performance of this
115 volt flexible heater woven and insulated
by the Holden Manufacturing Co., In-
dianapolis, Connecticut, for a classified installa-
tion. The multilayer thermal stability and
conductivity of Silastic is so great that the
heater will operate reliably in tempera-
tures high enough to boil the water at
which it is totally submerged.

Dow Corning 200 Fluid was selected as the
designer and after tests proved it to be the
most heat stable fluid available. Organic
fluids that rapidly when subjected to high
temperatures and to the heat generated by
excessive voltage loads, but Dow Corning
200 Fluid with its inherently dielectric in-
creased thermal slope, then only slightly
over 30 to 35 degrees centigrade operation.
This change is so slight that it is almost
completely lost by the expansion of the metal
parts and fittings.

Design Edition 11

DOW CORNING CORPORATION • Dept. DNEA
Midland, Michigan

Name _____

Title _____

Company _____

Street _____

City _____ State _____

ALABAMA • CHICAGO • CLEVELAND • DALLAS • DETROIT • LOS ANGELES • NEW YORK • WASHINGTON D. C. (Silver Spring, Md.)
Canada: Dow Corning Silicons Ltd., Toronto; Great Britain: Midland Silicons Ltd., London; France: Dow Corning Silicons, Paris

Versatile WESTERN GEAR Hoist



selected for new
Bell anti-submarine
helicopter!



When Bell Aircraft Corporation developed its new HSL-3 helicopter for Navy anti-submarine detection and rescue work, it selected Western Gear to design and manufacture the airborne hoist aboard the unique twin rotor aircraft. The Western Gear hoist lifts 800 lbs. at 50' per minute. The hoist shown in inset above, weighing 28 lbs. and similar in design to that selected by Bell, can lift 400 lbs. at 100' per minute, spooling more than 100' of 3/16" cable. By modifying the gear train it can lift up to 1600 lbs. at 25' per minute. A level wind assembly accounts spooling and the motor is equipped with radio noise filter to comply with AN specifications.



Western Gear's more than 40 years of experience supplying important components for aircraft is practically every description was a major factor in its selection by Bell to design and manufacture this vital hoist for airborne use. Knowledge obtained since 1933 enables Western Gear to provide a speedy, economical solution to any problem involving the mechanical transmission of motion or torque. Why not avail yourself of this experience to solve your problem? Western Gear engineers will be glad to offer their help and recommendations from your blueprints or specifications. Address: General Offices, Western Gear, P.O. Box 182, Lynwood, California.

"The difference is reliability" • Since 1933

WESTERN GEAR
ENGINEERS AND MANUFACTURERS

Plants at Lynwood, Pasadena, Belmont, San Francisco (Calif.)
Branches and Dealers - Representatives in principal cities

single program head and fixture which by means of punched tape, will be instantly changeable to accommodate a variety of gasket head types.

LMERD carries an automatic test philosophy one significant step beyond that of testing merely the individual sub-assemblies which make up a more complex equipment. CG has developed a unit which makes operational checks on completed equipment automatically, taking its operating instructions from punched tape.

The tape sets up various conditions of input, output, or load, then measures pertinent voltages, currents, etc., and prints out its findings. These too are accepted by computer and synopsized. The LMERD operational tester (see photo p. 72) has been in use for more than a year, Skiff says.

When used on new, recently completed LMERD equipment, the operational checker runs through 97 test items: checks, test network checks and 20 current parameter checks in less than 15 minutes, including several minutes of test data required for circuit value calculations. The same procedure used to take 60 minutes with conventional manual techniques. Added advantage is that the printed results of all test measurements record trouble shooting when a fault, equipment is encountered.



AUTOMATIC TESTER (1) speeds acquisition of test results; (2) shows assembled test fixture; (3), (4), (5) test points fully closed or complete.

Prior to making such quantitative measurement, the machine automatically checks shell against master stand only. At present, the unit can not be used for tests which involve an external value—such as impedance or impedance in certain types of equipment.

However, LMERD engineers are in developing techniques which they hope will enable them to automate the important phase of operational testing. About two years ago, in fact with CG's vast development program, the company split up its electronic

AMERICAN

THE GREATEST NAME IN

Inertia Reels!



American Seating Company produced the first Inertia Locking Shoulder Harness Safety Reel, and has been chief supplier to the Armed Forces since 1945. Continuing research and constant improvement have kept American Reels in the lead, designed to meet the most weight, size, and performance requirements of modern aviation units, and automobile and pool applications. These life-saving reels are also available for commercial planes. Our engineers will be pleased to consult with you on any inertia reel problem. Write to us—no obligation.

American Seating Company

GEORGE SAFIRE, 2, NEWARK • NEW YORK'S LEADER IN PUBLIC SEATING



56-DEVELOPED automatic functional tester (3) makes quantitative measurements of spot-solder characteristics of complete parts of equipment (2) and prints out test findings (1). Device gets operating instructions from punched tape.

Division's military activities into two groups:

• **LINEED**, at Utica, develops and makes test equipment, many of them for reference use.

• **IMEED** (Illico Military Electronic Equipment Division), Roseton, develops and manufactures large ground

log, or mobile equipment, such as air defense radar.

One object of the split along these lines was to divert the most highly competitive small equipment, which had themselves to produce low technology, from the manufacture of the larger equipment, which are used pri-


marily manufactured in much smaller quantities.

In some programs, such as a current one for a data link system, the two divisions take on the job jointly, with IMEED doing the airborne equipment and LINEED the ground-based. Sometimes other groups in the Electronics Division get into the act, including such facilities as the Advance Electronics Lab at Idaho, N. Y., and the new Microwave Lab at Palo Alto, Calif.

LINEED itself employs 150-275 graduate engineers. These are roughly divided equally among four engineering sections: radar and countermeasures; signal systems and devices; search radar and navigation; and advanced engineering.

Approximately 60% of LINEED's output goes to the USAF, 35% to the Navy (Gosler), and the remainder to miscellaneous customers. Most of that output is destined for aircraft or missiles.

Cut free from other groups in GE's Electronics Division, with three times what development efforts in large test-bed equipment and radio-TV sets, LINEED has been given the freedom and it shows the willingness, to its own approach aimed at creating a large size to compete favorably with small, low-overhead units.



PIONEERS IN BETTER PRODUCTS FOR GREATER SAFETY.

- **INSULATED DIAMOND CRIMP** Termination and Connectors for wire sizes #26 to #12. Used in engine applications.
- **ANFUSION** Pre-insulated Terminals and Connectors for wire sizes #16 to #10.
- **TERMINALING** and **COPALUM** Terminals and Connectors. The first attachable terminals for vibration resistance... for wire sizes #16 to #10.
- **Shielded Wire** eliminates the undesirable splicing of conductors and shields... for wire sizes #16 to #10.
- **CRIMP-THREAD HARD TOOL**—removes and replaces... compresses two attaching wires in #26 to #12 size with one stroke.
- **AMP AUTOMATIC WIRE TERMINATION**—makes thousands of perfect wire-to-board terminations per hour.

With them, as with all AMP products, AMP's thorough engineering results not only in reliability and precision of products but, ensure greater safety in the use of the end product.

ON THE AIR... ONLY THE BEST IS SAFE ENOUGH...

AMP

AIRCRAFT-MARINE PRODUCTS, INC., 2100 Paxton Street, Harrisburg, Pa.
In Canada: AIRCRAFT-MARINE PRODUCTS OF CANADA, LTD., 1764 Avenue Road, Toronto 12, Ontario, Canada.

© AMP

PIP...

"neat-as-a-pin" answer to BOEING B-47 service problems!

Standardization on PIP pins throughout the 1800-plus fleet of Boeing B-47's accomplishes quick-change servicing of essential electronics, photographic, landing gear, armament and safety equipment on board like of PIP double-acting, quick release, small no-locking pins in a wide variety of sizes reduces equipment maintenance and removal time... helps keep our jet fleet always on the ready!

an accepted part in industrial, military and aircraft designs—



Assemblies requiring disconnection and reconnection just right for PIP pins! They provide quick release and positive self-locking safety in a single unit in fixed or open applications. No extra pins, nuts, bolts or other separate retaining items or assembly tools are needed. Supplied in easy-to-handle or bag.

Complete literature available on request.

AVIATION DEVELOPMENTS INC.

Please send us pricing
PIP pin, S.S. 10-20

250 SOUTH VICTORY BLVD., HUNTSVILLE, CALIFORNIA

AVIATION DEVELOPMENTS (CANADA) LTD., TORONTO • AVIATION DEVELOPMENTS LTD., EDINBURGH, ENGLAND

If you have to hit a target
you can't see...

Call AC!

Not many people can build equipment that will let you hit an unseen target in flight. As a matter of fact there are very few who are experienced in this highly complex field. But, AC stands high on the list.

The U.S. Army's Skywarper is radio-directed and controlled by an amazing T-50 "electronic brain" built by AC. It not only directs and tracks intruders, it fires at them with devastating effect.

The deadly accuracy of the Skywarper is one more step toward precision fire-control weapons... just one of many steps taken by AC.

If you have a problem in the field of fire control, call AC today!

AC now has several openings for qualified engineers in the electronics field. For detailed information, write to us.



AT RYAN FIELD, GAITHERSBURG, MARYLAND
FEDERAL AVIATION ADMINISTRATION

AC
DEFENSE
PRODUCTS

Write for literature today!
"AC... Engineering for the Future"

NEW AVIONIC PRODUCTS

Components & Devices

• Subminiature, active resonator with 1.656 in. dia. x 1 1/2 in. long and weighing only 1 oz., comes in DPC73 model with cavity-tuned 5 meg. resonator band at 28.5 m.c. or 31.5 m.c. Unit



which operates over ambient temperature of -65 to 125°C, exceeds most heat requirements of MIL-R-6106A, and has minimum life of 100,000 operations at rated load. Electro-Mechanical Specialties, Inc., 6829 Melrose Ave., Los Angeles 16, Calif.

• Subminiature magnetron-generator, Type MC 5013, measuring 1 in. dia. x 2.425 in. long, and weighing 6.2 oz., puts out 125 volts/100 μ sec into a 100,000-ohm load. Speed is continuously variable from 200 to 8,700 rpm, with generator output reportedly linear over this range. Harmonic distortion is not dc 5%. Motor is a 315 x .480 cps 2-phase unit. Magnetic filament drops output shift to sec. out of focus position within 5 deg. arc/min. John Oates Mfg. Co., Avonlea Dr., 1 Main St., Racine, Wis.

• Low torque actuator which has low contact resistance is designed for operation at temperatures in excess of 500°F. Used with 10 amp. circuit and max. output current increases by




from 1 to 2 in. dia. x 2 1/2 in. long. Device can be used in a shop up to speed of 1,100 rpm. Electro-Tec Corp., South Hackensack, N. J.

• Transistronic magnetic amplifiers, less 60 cycle noise voltage and, is rated at 10 watts output. Two power transistors are gated by a magnetic amplifier, giving fast response. Used for a transistor pre-amplifier and stabilizing network. Amplifier can be operated up to 50°C, weighs under 10 oz., measures 1 1/2 in.

MALLORY-SHARON reports on

TITANIUM



MST 641-4V is primarily a bar and forging alloy, also has specialized sheet and plate applications.


NEW MST ALLOY

"stays put" at high temperatures

• The problem of elevated temperature embrittlement present with many titanium alloys has been overcome with this newest development. MST 641-4V (86% zirconium, 4% vanadium, balance titanium) can be used at temperatures up to 700°F with minimum creep or change of properties. It has excellent strength and stability at high temperatures, is relatively insensitive to notches, and can be hot worked over a wide range. It can be readily machined, welded, or heat treated.

Like all Mallory-Sharon alloys, MST 641-4V is vacuum double melted, assuring homogeneity and consistent quality. Specify it for consistent, predictable, high temperature performance. A bulletin listing complete data is yours for the asking. Write Mallory-Sharon Titanium Corporation, Dept. B-4, Niles, Ohio.

MALLORY  **SHARON**



READ WHAT HAPPENED WHEN WE PUT OURSELVES IN THE "ENVIRONMENTAL TEST CHAMBER"

Both the Electronics and the Air Arm Divisions of the Westinghouse Electric Corporation are expanding. We need experienced electronic engineers for advanced design and development work — so we put ourselves in the "environmental test chamber" to see just what we have to offer the people we need.

We found that we have a professional atmosphere that is what the engineer needs. We offer advanced study in company expense and many promotions that mean a good future.

Our unique and flexible advantages started right in this test room. Finally, there were many others like the Westinghouse Talent Award Program, that make us one of the most dynamic organizations for all electronic engineers.

APPLY NOW—

Openings exist in the fields of—
COMMUNICATIONS ENGINEER, DEFENSE
(Missouri) MISSILE GUIDANCE
R&E CONTROL FIELD ENGINEERING
RADAR TECHNICAL WRITING
COMPUTERS

TO APPLY—

Send resume reflecting education and experience to:
Technical Director
Dept. 302
Westinghouse Electric Corporation
2617 Wilkes Avenue
Baltimore 1, Md.

ILLUSTRATED BROCHURE

WILL BE SENT TO
ALL APPLICANTS.



dist. 4 1/2 in. long. Lithoscope, Inc.,
508 Western Ave., Cleveland, Ohio

• Commercialized since mid-60s, a new series of low-inertia 2-phase 6-pole 400-cycle types can be operated at temperatures of $\pm 150^\circ$ to 160° at altitudes up to 50,000 feet. Units are available in various speed/torque combinations and can be obtained with an integral tach generator if desired. Motor encases 1 in. dia. 3.54-in. long. Eclipse-Powers, Div., Bendix Aviation Corp., Teterboro, N. J.

• Solid-state double clip, reportedly designed to hold 5000 of all standard 14-pin sockets in their slots, push-in sockets, and other uses. Units are made from brilliant copper base.



plated with gold when in electroless Nickel Products Engineering, Inc., 4000 Long Beach Ave., Los Angeles 25.

Transducers

• High temperature pressure and acceleration pickups can be operated at temperatures as high as $2,200^\circ$. Model 2145, for measuring dynamic pressure, reportedly has flat frequency response from 2 to 5,000 cps, and is available in several pressure ranges up to 5,000 psi. Output is 40 mv/psi at the lower range. Model 2124 accelerometer has flat frequency response between 2 and 4,000 cps. Output is at least 10 mv/g. Piezores is made for solid piezoelectric elements with fluid or air as both inputs. Endevco Corp., 193 East California St., Pasadena 1, Calif.

Laboratory Equipment

• Ultraphase power supply Model 180, supplies 500 v.a. of 500 to 500 cps power into a delta connected load. Output voltage can be varied from 100 to 136, with 1% regulation from no load to full load. Maximum distortion is limited at less than 7% under full load. Model Engineering Corp., 130 So. Elm Oaks Ave., Pasadena, Calif.

• Deskbridge Model 218 is a schematic bridge packaged and referred to the manufacturer's local economic club, provides single line equivalent to four phase for impedance of 0 to 12 megohms or series differential impedance

DE HAVILLAND OTTERS

The new "Voyagers" of the Canadian North



2000 lbs. payload for 1000 miles range

For Information Brochure: Write Dept. HW-1

THE DE HAVILLAND AIRCRAFT OF CANADA LIMITED
POSTAL STATION 1 TORONTO, ONTARIO



SEWING STEEL TOGETHER with 4-million-volt stitches

Pieces of steel as large as railroad-car axles are being welded with speed and efficiency in the Cleveland Pneumatic plant.

The world's largest and most powerful general-purpose flash-burst electric-resistance welding machine is joining aircraft components now. This machine can butt-weld high-alloy steel pieces having a total cross-sectional area of as much as 67 inches. With low-carbon material, the area can be as large as 109 square inches.

A limited amount of this machine's extra time is now available on a contract basis to produce highly quality large-area welds on high-alloy steel at low unit costs.

Write for Booklet C-855 which describes this machine and its capacities, and also tells you how our Contract Welding Department can be integrated with your production.

Cleveland Pneumatic Tool Company

Registered: 0490
221 East 17th Street • Cleveland 3, Ohio
MAIL-ORDER DEPARTMENT • AIR-MAIL ORDER AIRCRAFT DESIGNER'S HANDBOOK COMPANY



AT CLEVELAND PNEUMATIC THESE FACILITIES CAN ALSO WORK FOR YOU



MACHINING

Your welding assemblies can also be given almost any machining or finishing that you require when they are contract-milled at Cleveland Pneumatic. Our modern machine shops include all types of turning lathes and sawlathes, from grinders that cut over 25 inches in diameter and 87 feet long to micro-process thread grinders capable of producing any accuracy-quality threads on parts up to 12-inch-diameter.



BEST-TREATING

A large and experienced heat-treating department can give your contract-milled parts the type of best treatment that is required. Great heat-treating furnaces and quench tanks 18 feet deep can handle alloy-steel parts up to 15 feet in length.

Cleveland Pneumatic Tool Co.,
221 East 17th Street • Cleveland 3, Ohio

range. Reversible, can be used to weld in 0.001 inch on lowest scale. Micro range instantaneous current 0.01% with reference zero. Electro-Measurements Inc., 4132 S.E. Stark St., Portland 15, Ore.

• Regulated power supply, Model 702B, provides up to 200 ma. at 0 to 600 volts continuously variable, with regulation of 1% or better and ripple less than 10 ma. peak-to-peak. Variable negative output of 0 to 150 volts is provided for bias, as well as 5.1 v. at 5 amp. for filament supply. Shasta Div., Beckman Instruments, Inc., P.O. Box 290, Richmond, Calif.

Engineering Aids

• Muckitt, for use by screenmakers, wire designers, contains a variety of gage, cloth, screen, draper, supports, a detailed chart, and other useful facts.



ing blocks which enable speedy construction of laboratory models. Model 624 comes in three different sizes. Servomechanisms Inc., 615 Main St., Westbury, L. I., N. Y.

• Pulse transformer L-6, Cat 10871 contains five different kV type pulse transformers, with primary inductance values ranging from 0.5 mH to 50 mH, and turns ratio as high as 8:1. Engineering Division 927 goes directly on transformer, and is manufactured by Squigg Electric Co., 127 Marshall St., North Adams, Mass.

397170 FILTER CENTER 000333

• Electronics Output Because-The electronics industry is expected to turn out \$6.2 billion in units and component products this year, compared to \$1.8 billion last year according to a mail survey in the Electronics Digest.

• New Test Facilities—Complete an unattended test facilities for checking screw components and devices to MIL spec are available at American Electronic Laboratories, Inc., 661 Arch St., Philadelphia 6, Pa. Four-page brochure containing facilities is available.



Progress is being made in the Applied Nuclear Field at CONVAIR — Fort Worth — in nuclear analysis, design and experiments even, including the fields of shielding, radiation effects and nuclear aircraft technology.

As an integral part of General Dynamics Corporation's program of pioneering in Nuclear Fields, CONVAIR's services afford exciting opportunities for engineers and physicists to enter into Nuclear Development in its most advanced stage.

CONVAIR'S Nuclear Program affords highly rewarding career opportunities both by way of professional accomplishment and personal income. A company sponsored, on-going program enables candidates to earn graduate degrees in Nuclear Engineering.




Just Write to the Conquest Division for an check degree of freedom and dry, both in confidence to achieve being well and success. Within a few hours days of Fort Worth you can begin to work with people who are looking for the future and other water ways.

For further details write M. L. TAYLOR
CONVAIR Engineering Personnel Dept. ER
Fort Worth, Texas



CONVAIR
A DIVISION OF GENERAL DYNAMICS CORPORATION
FORT WORTH, TEXAS

EQUIPMENT



IMRA PYROMETERS: Left, a double-sided pyrometer attached to motor cabinet. At right, single-sided pyrometer on shroud.

Pyrometer Aids Jet Engine Control

The development of a compact and reliable pyrometer to measure, accurately, and almost instantaneously, the temperature of burner and hot gas in the 1,000-7,000° range, was announced recently by the Westinghouse Research Corp., in New York. Plans already are underway for the construction of a ground test for flight testing.

The temperature range of a heat engine defines its thermal efficiency. Therefore an instrument that measures temperature accurately and quickly and can exert a useful influence can be used as a heat engine control.

The IMRA Pyrometer measures heat radiation and translates these into temperature readings which are processed in milliseconds and stored in RAM.

Known as an IMRA (Infrared Microchromatic Radiometer) Pyrometer, this instrument has practically no input temperature dead weight that is what the gases discontinue, and will be designed large compact enough to be airborne. WASSR sensors on the shroud will handle the pilot or heat engine control logic and more accurately than the thermocouples which have been in use since the invention of jet engines.

Because heat, at the thermocouples, is slow, and the low-temperature reading has to be sent to the pilot who then operates the engine accordingly. WASSR hopes the IMRA Pyrometer, developed after eight years of research, will be capable of controlling a jet engine directly, bypassing the pilot entirely.

Thus, for two types—single-sided and double-sided—have been developed, both

based on the principle that hot gases emit radiation in specific bands in the visible infrared region of the spectrum. This radiation is a characteristic of the hot gas temperature.

Single-Sided IMRA

The single-sided IMRA is the type WASSR plans to develop into control devices for hot gas engines such as turboprops. Use of temperature in a control system becomes important when dealing with engine types at extreme power settings which have no other control parameters.

Among these are afterburners, ramjets and rockets.

Heat in the burner behind single-sided IMRA. Radiation of a hot gas varies with three factors—rate of production of gas and gas temperature. Since all jet engines pyrometers will have a feedback loop that will make the type of gas—its known and rate be constant for it.

New variable to eliminate a quantity of the gas, it is particularly in the case of IMRA's development that WASSR scientists did much original research and now their computer aids the first to establish the possibility of determining the absorptance factor of gas in order to correct for the effect of gas quantity.

Since the hot gas path in a jet engine is fixed and the absorptance factor can be predetermined, the factors can be incorporated in the instrument's electronics and thermalized in a variable. Thus, two of the three variables have been controlled and the instrument will indicate only the third variable—temperature.

Research leading to solving the prob-

lem of predetermining the absorptance factor was completed by a third dimension. The absorptance factor now, a IMRA is comparable to the absorptance coefficient still known in conventional pyrometers.

The big problem that WASSR team has had to solve now that of dealing with consistency in depth—the varied hot gas streams of a jet engine exhaust.

IMRA Operation

A single and is mounted at or near the front or hot gas stream and the main requirement is a small aperture through which gas radiation can reach the instrument. This need not be mounted directly in the stream, as a red pipe or even a combustion chamber. If the work means an excessive heat or speed, considerations, the instrument must be remotely mounted, this can be done and radiation directed at it with a mirror.

Infrared, infrared radiation from flame or hot gas is collected in the instrument's optical area by a monochromator, a pyrometer device which splits gas radiation into its spectral components. A narrow region of this spectrum is selected by a slit which allows only the small part of the spectrum's radiation to impinge upon a radiation sensor element. The element then sends a signal which is electronically amplified and converted into a temperature reading.

IMRA Advantages

8. Types WASSR's chief objective, after these initial advantages of the IMRA Pyrometer.

• No flow interference: The IMRA Pyrometer, being outside the gas



Boeing engineers have a date with the future

Can't make it this Boeing B-57, IM-59, an increasingly important in America's defense planning. Many kinds of engineers—civil, mechanical, electrical and aerospace—play vital roles in developing it. The knowledge they are gaining will be priceless in producing the legendary vehicles and guided missiles of the future. They may explore the frontiers of engineering knowledge in rocket and nuclear propulsion, in control systems of vibration, temperature and pressure and in many other fields.

Boeing engineers are members of America's top defense team. The aircraft they help develop will maintain the leadership and prestige established by the Boeing B-47, the present "bullethead" of Strategic Air Command... the B-52,

our next new global bomber, the Boeing B-70... and, most recently, the B-58, the first jet reconnaissance.

At Boeing, engineers' professional achievements are recognized by regular merit increases and in other ways. The Boeing policy is to promote from within the organization. And Boeing is known as an employer company. One out of every seven employees is an engineer. Having top management, the profession is more higher.

Equipment is Boeing is superior the latest electronic computer, a chamber that simulates altitudes up to 100,000 feet, speedily equipped laboratory and the new multi-million dollar Flight Test Center. The world's most versatile pressure vessel wind tunnel at Boeing,

is soon to be supplemented by a new tunnel capable of velocities up to Mach 6.

Do you want a career with one of America's most varied engineering companies? Do you want a chance to grow, and to share in the challenging future of flight? Then there's a place for you on one of Boeing's engineering teams in design, research or production.

- JOHN C. LAMBERT, Staff Engineer—Personal
- Boeing Airframe Co., Dept. C-42, Seattle 16, Wash.
- Please send further information to my nearest
- I am interested in the following of a circle
- with Boeing
- Name _____
- Address _____
- City _____ State _____ Zip _____
- Telephone _____
- Title _____

BOEING
Aircraft Leadership Since 1916
SEATTLE, WASHINGTON WICHITA, KANSAS

NEW HIGH ALTITUDE MAGNETIC RECORDER

THE AIRBORNE AMPLEX 800 records the broadest combination of data ever obtained concurrently on one magnetic tape—performs under all high altitude environmental conditions—and furnishes data compatible with the most widely used playback equipment.

HANDLES ANY AIRBORNE DATA REQUIREMENT

The Ampex 800 now provides from 1 to 28 data channels. By attaching optional amplifier units, each one can be adapted to any one of three basic magnetic recording techniques:

Direct recording—300 to 35,000-cycle response for a wide-band data or multiple recording of RCB subcarriers.

FM-carrier type recording—D-C to 5000 cycles and high instantaneous accuracy suitable for shock and vibration data.

Pulse-width modulation recording—Up to 30 equivalent readings compressed on to each tape track; frequency response 0 to 5 cycles/sec.

Combination of these recording techniques can be provided to satisfy practically any flight test requirement by simple insertion of the proper plug-in amplifier. Separate channels can be assigned to measurements requiring wide band response or high transient accuracy. By using pulse-width techniques, many relatively slow instrument readings can be compressed on to a single channel. All will have a common time base.

WITHSTANDS THE RIGORS OF HIGH ALTITUDE FLIGHT

The Ampex 800 will perform within specifications under vibrational forces as high as 10G—temperatures over in temperature range from -65°F . to $+125^{\circ}\text{F}$. is unaffected by altitudes to 50,000 feet—and withstands a relative humidity of 100% up to 125°F . The Ampex 800 is light in weight: it operates on 27.5 volts D-C and 115 volt, 400 cycle, A-C. All operating functions can be remotely controlled.

RETAINS WIDELY ESTABLISHED RECORDER STANDARDS

The majority of all magnetic recorders now in test—mainstream use are Ampex machines. Their recording characteristics, tape speeds, track widths and other parameters have become a standard in aircraft and missile testing. The Ampex 800 retains these standards while greatly extending the environmental and mechanical conditions under which accurate test data can be gathered.



Performance specifications, descriptions and explanations have recently been furnished by the space on this page. A full description and detailed specifications on the Ampex 800 are available by writing Dept. UU-2242.

First in Magnetic Tape Instrumentation

BRANCH OFFICES: New York, Chicago, Atlanta, San Francisco, Dayton, College Park, Maryland (Via Hughes D-C unit)

AMPEX
CORPORATION

REPRESENTS: A. R. Shaw, Inc., Boston; King Quality Magnetic, Inc., Worcester; Instrument Engineering & Equipment, Irvine and Irvine, California; General Electric Company, Canada

1000 S. MAIN ST., SANTA ANA, CALIF. 92701
NEW YORK OFFICE, 30 EAST 42ND ST.

vision, does not interfere with flow as do thermocouple probes which protrude into the gas path. Now is the instrument subjected to the aerodynamic effects of very hot, high speed gases.

• **No air leak.** Instrument is not cooled by the hottest gas temperatures obtainable.

• **No multiplexing.** The IMRA device, receiving radiation throughout the width of the gas stream, averages the temperature. One unit does the work which normally would require several thermocouples, since each probe, senses the gas temperature at its location only.

• **Short delay.** Response at a few, well seconds is obtainable with the IMRA device as compared to one or more seconds response time for thermocouples.

• **One variable.** Only Variables present in hot gas streams, such as velocity, mass flow and turbulence, do not influence the IMRA unit as they do thermocouples.

• **No corrosion.** IMRA does not require correction, after corrosion, to take care of such factors as radiation losses, which affect thermocouples.

Here is how Al Grossman, chief engineer, delineated IMRA's first heat fit. "Intensity of radiation varies with the temperature of the gas in a well defined manner. For a moderate change in temperature, you have a large variation in radiation, this makes the IMRA Promoter extremely sensitive. Moreover, the higher the temperature being measured, the greater the variation of radiation. Therefore, the instrument becomes progressively more sensitive as temperature rises."

Double-Sided IMRA

WASH developed the double-sided IMRA Promoter before the single-sided unit. This feature has inherent delicateness as a potential airborne instrument because of its size, weight and relative complexity.

But when the double-sided IMRA found a decided need as a laboratory instrument for fires and hot gas measurement, WASH developed the device to the point where it is now suitable as a standard instrument.

IMRA Status

The company, that has solved the theoretical and practical problems of reheat-heating double-sided IMRA and is prepared to go ahead as orders are received.

W. S. Fandler, company president, said research and development of the single-sided IMRA as a laboratory tool has been accelerated. He now wants to integrate the instrument with a set engine to solve such remaining prob-



(See you at the Western Show, Booth 1417-1418)

THESE ARE ALWAYS OUR DESIGN
OBJECTIVES IN BUILDING PRECISION

COMPONENTS

GYROS • SYNCHROS • SERVO MOTORS

From the time drawing pencil first touches paper, every step we take with E-P precision components is geared directly to combine with Vibration Systems.

No one can be sure that our Gyros, Synchros and Servo Motors will deliver required accuracy and performance under all kinds of operating conditions.

Write, now or call us for information on standards and special design, pricing, and delivery. **RESEARCH ENGINEERING DIVISION, VIBRATION SYSTEMS CORPORATION, TRENTON, N. J.**

Eclipse-Pioneer
DIVISION

Bendix
AVIATION CORPORATION

Mail Order Office: 117 E. Washington, Suite 201 • Export Sales: Bendix International Division, 200 E. 43rd St., New York 17, N. Y.



THE WORLD'S LARGEST
PRODUCER OF
READY-TO-INSTALL POWER
PACKAGES FOR AIRPLANES
INVITES YOU TO ENJOY YOUR
WORK AND YOUR LIFE IN

beautiful
SOUTHERN
CALIFORNIA

We believe we can offer you an opportunity to improve your position in the business world—and improve your way of life here at Rohr Aircraft Corporation in beautiful, temperate, exciting Southern California. To strengthen our personnel in various departments, Rohr has a real opportunity for you if you are skilled as an —

ENGINEER
(Aircraft Design or Structures)
LOFTSMAN
JIG & FIXTURE BUILDER
TOOL PLANNER • TOOL DESIGNER

ROHR
AIRCRAFT CORPORATION

Please write giving complete details and we will answer immediately.
Mr. Ned DeVries, Personnel Department
Rohr Aircraft Corporation
Owls Vista, California

* 10 miles south of San Diego on scenic San Diego Bay

less as how to mount the unit, its needed configuration and size and how it can be tied into the engine's control system. Power requirements are 30 watts a c.

WSSB is about to establish a program to build a small unit, first for ground test engine work only. Next step will be to further miniaturize the unit work out on "bugs" and produce an instrument capable of working reliably as an engine device, which is Tandler's ultimate goal for the single-sided IMRA.

Twenty Years Ago

Tandler started his business twenty years ago doing research and development in the field of electrical and electronic controls for aircraft tools and automatic measuring instruments. The organization, then called Industrial Scientific Co., was located at the same address as today's south-eastern airport, 51 W 134th St. New York. Business gradually grew until, in 1934, he made an arrangement with the Warner & Swasey Co. and formed the present Warner & Swasey Research Corp. as a partially-owned subsidiary of the parent company. Today the organization is doing research and development in the fields of instrumentation and controls for special equipment, including Warner & Swasey.

At the same time Tandler is pushing his IMRA instruments. He is also producing periscopes, a blood pipe lens and he took part engine work between at Ford Aircraft Engine Division, Chicago.

OFF THE LINE

Bobb Co's instrument division has signed a contract to overhaul all instrument for Business Airlines in its new plant at Sky Harbor Airport, Phoenix.

Lockheed Aircraft Service—Intertec Inc. has started work on two new contracts for the Aviation Supply Office, U. S. Navy. Chapman is overhauling 14 main components of oil-pressure-charger drive shaft disconnect assemblies for an undischarged number of RV, WV1 and WV-2 Super Constellation aircraft.

All commercial airlines in the U.S. are now using an auto-rotated tire according to the First. First commercial airline tire installation was made in mid-1944.

United Air Lines is adding a fourteen-larger and new flight tickets to its Seattle Tacoma Airport facilities at a cost of over \$1 million.



Off of Boeing planes, Navy Photo

engineers for ARRESTING gear and catapult developments

Here is an opportunity to participate in a vital All American program—the design and development of arresting gear and catapults. At All American you will work in the finest hot shop in the country for the most unusual work.

The research program is typical of the engineering services available at AAE. You'll be in the shop phase of All American's for various projects. Currently on the boards are in production are projects which include control types of switches for aircraft and engine use, air pickup equipment, fuel injection systems, improved landing gear and portable measuring stands.

All American will give you an unexcelled chance to make a major contribution to aviation development.

YOU AND THE ALL AMERICAN PROGRAM

All American offers a complete expanding and development service to the aviation industry and the military. As part of the AAE staff you may find yourself involved but never either bored or ignored. A young firm, directed by a sound and progressive management, All American is big enough to provide ideal working facilities and small enough to recognize individual merit. Don't miss your opportunity at AAE today.

THIS IS ALL AMERICAN



The Arresting Gear for runway use checks, energy by drawing a steel cable through a stationary brake block.



Dynamic made model airplanes are used by AAE in the design and development of emergency engine services.



The jet propelled test set was designed by AAE for the development of arresting gear and launchers.



RESEARCH • DESIGN • MANUFACTURE
All American Engineering Company
DUPONT AIRPORT • WILMINGTON, DELAWARE

Zoomability

1218 E. 112 St., Cleveland 10 Ohio
 DuPont development subcontracting
 equipment handling, Perkins Products
 Products Inc. Shoreline 1, N.Y.
 ... Set Your Sights on Tape, color
 tanning film, Perkins Products, 223 W.
 Adams St., Chicago 11, Ill. ... Colman
 an diamond tool for specialized grinding
 wheel dressing operations, Getling
 DT-35, Diamond & Tools, Inc., 19515
 John R. St., Detroit 3, Mich.

Walking-type-Holden TTF 20 pullet
 track, Industrial 5712, Barrett-Cramer
 Co., 626 Dundee Rd., Northbrook, Ill.
 ... Direct Angle and rack measuring
 work, data chart, Steps Equipment Co.,
 451 S. Dearborn St., Chicago 5, Ill.
 "Design File" for miller-plasma, CDC-717A,
 General Electric Co., Pittsfield, Mass.

Business plane overhaul and service
 facilities, handling, Southwest Aero
 Inc. Co., Love 1466, Dallas, Tex.
 Background data on the Advisory
 Group on Electron Tubes, in support
 of the Assistant Secretary of Defense
 for Research and Development, Inc.,
 New York University, Southwest
 Advisory Group on Electron Tubes, 516
 Broadway, New York 13, N.Y.
 Design Manual for High-Strength
 Steels, U. S. Steel Corp., 325 W. First
 Penn Pl., Pittsburgh, Pa.

MAXIMUM BOOST
 WITH
 MINIMUM LOSS
 AFTERBURNERS
 BY...


marquardt AIRCRAFT CO.
 Van Nuys, California

THE WORLD'S LARGEST JET ENGINE RESEARCH AND DEVELOPMENT CENTER



Canadian Jets for NATO
 Fourteen-hand F-4E Sabre jets over the
 RCMP Station at St. Hubert, Quebec.
 Built in Canada, they will join other Cana-
 dian airplanes serving with NATO.

Sand strip - Seamew base



*Amphibious design means simplicity
 of maintenance and recovery in
 combat and ease in use of space and
 equipment. Seamew's hull is made
 completely ready for use.*



*The wheels of the Seamew can be
 easily changed, with differing ease of
 type in use of a surface from which to
 operate.*



*Seamew's hull surface contributes
 to the low landing and landing
 speed. The Seamew requires
 the minimum length of runway
 for emergency landing or rescue
 recovery.*

Seamew—a tough, economical, all-weather
 anti-submarine hunter. Airborne in a short distance from
 any rapidly constructed airstrip—or even a stretch
 of beach—the Seamew can conduct a maritime
 search with up-to-date radar equipment and use a
 variety of weapons to effect a kill. Its high
 maneuverability, low stalling speed and fixed shock-
 absorbing undercarriage enable the Seamew to land
 back safely after operating in weather conditions
 impossible for other anti-submarine aircraft.

**R.A.F. Coastal Command
 to be strengthened with SEAMEWS**

—British Defense White Paper

Design commenced April 1952

First flight August 1952

Now in production for the Royal Air Force
 and the Royal Navy.

Short Brothers & Harland Ltd., Queens Island, Belfast, N. Ireland. The first manufacturers of aircraft in the world

NEW AVIATION PRODUCTS

NEW AUDIO AMPLIFIER



Meet a practical audio amplifier for cockpit & cabin speakers at a great price. Weighs only 2½ lbs. Two channels. Call, write or visit today. Moderate delivery.

SPECIFICATIONS
14-w. with 15 ohm
4000-ohm 4 x 40
100 mV
100 Hz. 100 Hz. 100 Hz.
100 Hz. 100 Hz. 100 Hz.
100 Hz. 100 Hz. 100 Hz.
100 Hz. 100 Hz. 100 Hz.
100 Hz. 100 Hz. 100 Hz.
100 Hz. 100 Hz. 100 Hz.

AVIATION
AAA
ACCESSORIES

P.O. Box 4171 • Fort Worth 4, Texas



MILLER DEVELOPMENTS
...designs for
greater mobility

PRODUCING: Army M101
Infantry M101
PRODUCING: New High Principles
Advanced Principles
Methods

Which Miller just the industry in
new developments.

MILLER HELICOPTERS
PALO ALTO, CALIFORNIA



Compact Endoscope Camera

Compact endoscope camera provides accurate, real-time photographic records of CRT phenomena for direct exposure of the scope image.

Endoscope 1414, based on an adaptation of a small Polaroid fast print camera, mounts easily on standard three or four-inch scope. Scenography (lens and mounting plate) is available in packaged assembly group.

Arrive 1414 can record three exposures on one 2½ in. by 3½ in. print. Arrive Associates, 16 S. San Gabriel Blvd., Pasadena, Calif.

G&L \$1 Million Tool Exhibit

Giddings & Lewis \$1 million exhibit at the National Machine Tool Builders Association show, International Airport, Chicago, Sept. 6-17th, will be highlighted by these new machines:

- **Hydro extra-heavy double housing** phase will be shown working cut and steel at 400 ft. per minute tool speed. Dual saddle and slide controls power cross feed to side heads drive and sleep and extra high pressure tool when are featured. High horse power adjustable voltage source drive has a table speed range from 25 to 400 ft. per minute. Hydraulic table top control, automatic table movement.

- **400 FTAR** supercharged horizontal borer, drill and miller has six inch diameter spindle and 10-hp. an active on headstock for direct drive to spindle. Spindle has 32 speeds from 5 to 830 rpm. Telescope directional reading system are on headstock, universal and working systems. All accessories are standard, special power tool headstock base tool.

- **370 FTAR** free-type, high-power precision horizontal borer, drill and miller set work each meter spindle and a built in modern support only the headstock, which increases the machine's accuracy, tool capacity. Op-

erator's elevator permits him to adjust tool working position.

- **Slack vertical turret lathe** with directional control of feed and traverse movements and "journal" system provided remote control shift. Each head has independent feed and traverse. Swirling turret and tool heads are counterbalanced for new motion. A 50 hp. motor drive and over-hill top pump for cooling at high speeds and heavy loads are also featured.

- **Eight-foot heavy-duty vertical boring and turning** mill has long-type construction housing and extra heavy bed and table cast to hold 55 tons. Speed-range covers 10.700 (rpm). Constant surface speed and chip thickness control mechanisms are included. 75 hp. adjustable voltage drive provides wide range of table speeds.

- **10-in. 400 FTAR** phase-miller has four heads, each with a 50 hp. water cooled motor and 24 spindle speeds from 9 to 930 rpm. Heavy section table is driven by a d.c. motor through a



combination drive, worm and wheel and double gear gear on each screw work. Operator can position heads by remote control. Rigid clamp loading of sliding jaws gives total support from center to machine frame.

- **"Tach-cool"** adaptoring system is used to regulate temperature in lubrication temperature to outside, with ambient or operating temperatures.

- **100 RT horizontal** borer, drill and miller features 30-in. x 35 in. sliding work table. Spindle speeds range from 7 to 1,600 rpm.

Giddings & Lewis Machine Tool Co., Fort Lee, N.J.

Machine Speeds F-100 Wiring

Automatic aircraft wire parasitic machine produces circuit wiring to use operation and requires only one operator. The unit, used at North American Aviation's Los Angeles plant, was de-

THE NEW ARV MARY MATH 2-SP. TRICAL BOARD IS EQUIPPED WITH THE ARO 2 LINE SQUAD OXYGEN CONVERTER.



ARO Vision-eering LEADS THE WORLD IN OXYGEN EQUIPMENT

Another ARO FIRST! The new 1, 2 and 22 Line Liquid Oxygen Converters developed by ARO from the space and weight load in turbojet and bombers... for example, crew oxygen increased by 75 to 100 percent... present oxygen supply as an oxygen in weight. Complete technical and engineering data available on request.

There is a report of many ARO contributions to aviation progress... with world leadership in the design, development and manufacturing of oxygen equipment. Leading aircraft builders today depend on ARO for a growing number of precision products. For further details write:

THE ARO EQUIPMENT CORP. • 4014 VAN CLEVELAND, OHIO
An Engineer of California, Los Angeles, Calif.
An Engineer of Canada, 14, Toronto, 14, Ontario
Office in New York, New York

ARO

AIRCRAFT PRODUCTS

Head Office: Toronto, Canada
Branch Offices: Chicago, Ill., New York, N.Y., Los Angeles, Calif.,
San Francisco, Calif., Dallas, Texas, Houston, Texas, Phoenix, Arizona,
Albuquerque, N.M., Salt Lake City, Utah, Denver, Colorado, Portland, Oregon, Seattle, Washington, Tacoma, Washington, Vancouver, British Columbia, Canada.



THE FREE WORLD FLIES

IF ANY ONE aircraft engine can be called the standard of commercial aviation in the free world, it is the dependable Double Wasp built by Pratt & Whitney Aircraft.

This 18-cylinder power plant, designated the R-2800, is installed in more than 1000 of the free world's modern, commercial airliners now in use or on order. Seventy-two airlines, and many large business fleets, are equipped with aircraft powered by Double Wasps. Included among these are all the models of the four-engined Douglas DC-4, as well

as all two-engined Convair and Martin airlines.

Like the earliest Wasp engine of 1925, and the famous engines of succeeding years, the 2800 hp R-2800 is outstanding for its power, its efficiency, and its clean-running dependability.

These are the power plant qualities that make Pratt & Whitney Aircraft piston engines first choice for nearly 90 per cent of all commercial aircraft. They are the qualities that have helped create and maintain an unrivaled position for America's commercial aviation.



DOUBLE WASP engines power three of the most widely-known aircraft types. Included are all models of the four-engined Douglas DC-4, all two-engined Convair and Martin airlines. In airline and private commercial service

throughout the world, these aircraft have achieved an outstanding record of dependability, efficiency and safety. Double Wasps now power over 32 per cent of all commercial airlines.

WITH THE DOUBLE WASP



SEVENTY-TWO AIRLINES, operating in every part of the world, depend on aircraft powered by Pratt & Whitney Aircraft R-2800 Double Wasp engines. Most variations of the engine, like that pictured here, develop 2500 hp for takeoff. Double Wasps are standard for three of America's most widely known aircraft types.



ONE OF THE DIVISIONS OF
UNITED AIRCRAFT CORPORATION

Pratt & Whitney Aircraft

HIGH SPEED AND PLANT EAST HARTFORD, CONNECTICUT • BRANCH PLANTS: NEW YORK, BOSTON, WASHINGTON, MEMPHIS
In Canada: Contact with Pratt & Whitney Aircraft Co. Ltd.

46 Major Projects at Lockheed

Advance Careers of Engineers

Lockheed projects cover virtually the entire spectrum of structural and engineering endeavor, including air-to-air, air-to-ground, and jet transports, jet fighters, trainers and bombers, vertical wing aircraft, nuclear applications to aircraft and many other significant classified projects.

It is the largest development and production program in the company's history, with 13 models already on assembly lines.

Diversification such as the other projects:

- More opportunity for promotion—because there are more high selection positions to be filled on such a large number of projects.
- More career mobility—because Lockheed activities span so many phases of structural effort.
- More stimulating work—because there is a wider range of assignments, because engineers have more scope for their ability, because a firm active on so many fronts of constant welcomes and rewards fresh thinking, new ideas.

Generous travel and moving allowances make you and your family as glad Lockheed as you are to join it.

Lockheed Employee Service helps you get settled when you arrive.

Immediate Openings for Aeronautical Engineers:
AERONAUTICAL ENGINEERS • MECHANICAL ENGINEERS • ALL levels of mechanical, electrical, hydraulic, power plant, controls and structures fields. • ENGINE TEST AERONAUTICAL ENGINEERS • MECHANICAL ENGINEERS • TO WORK ON Lockheed's new 701 Digital Computer. • MICRO WAVE ENGINEERS • WORK ON FOUR THOUSAND DIVER EXPERIMENT AS AN ADVISORY CAPACITY ON AIRCRAFT RESEARCH APPLICATIONS AS WELL AS A BROAD THEORETICAL BACKGROUND AND AN ADVANCED DEGREE IN ENGINEERING OF PHYSICS • OPERATIONS RESEARCH SCIENTISTS • STRUCTURAL ENGINEERS • STRUCTURAL MECHANICAL ENGINEERS • THERMODYNAMICS ENGINEERS • WEAPON ENGINEERS

A report on "High Heat Test Steel" taken from one of Lockheed's monthly engineering and manufacturing forums is available to interested engineers. Address requests to the Forum chairman, Z. M. Spunkling.

Engineers interested in Lockheed's expanding development and production program are invited to write to:
E. W. De Larrues, Dept. ME-5-E.

Below: Lockheed engineers at work on various projects



Engineers at work on a large spherical object.



An electronic engineer at his workbench.



An engineer working on a large turbine.



A Lockheed engineer working on a large turbine.



Engineers at work on a large spherical object.

Lockheed
AIRCRAFT CORPORATION
CALIFORNIA DIVISION • BURBANK
California



An engineer working on a large turbine.

applied and built under an Air Material Contract.

Annual dollar savings, based on new production rates for jet fighter planes at North American, by one machine, will add about a week on delivery to \$42,140.

The machine measures, surfaces at both ends, cuts and end stops multi-mill plan head and cloth single end ducts over. Changing from one order to another takes about one minute, and from one gage to another about five minutes.

Amec Engineering Co., Milwaukee, Wis.

ALSO ON THE MARKET

36-6780 electro-magnetic clutch holds sprockets without slip rings or centrifugal and is designed for use with 480-cycle 115v a.c. induction motors. Beale loading torque is two pound-inches, clutch torque, two pound-inches, 11,000 rpm, four revolutions come from the speed—Clutch for larger motors and with ratings to 25 hp as at 11,000 rpm, are being tested for future production.—Air Associates, Inc., Yonkers, N. Y.

Meltrape is production battery-operated cartridge-loaded type recorder. Meltrape says it has applications in small business records in during flight tests of small planes. Price \$249.95.—Meltrape, Business Machines Corp., 944 Bixby St., Brooklyn 99, N. Y.

Nitrogen charging valve has increased area sections at critical working areas and is designed for 5,000 psi working pressure and 20,000 psi burst pressure. Valves have applications in landing gear, vacuum cleaners and similar projects.—Superior Hydraulic Division, Superior Pipe Spooling Co., 15201 St. Clair Ave., Cleveland 10, Ohio.

Refrigeration cooling or heating units for electronic equipment are oil-free, tested and controlled. Cooling and heating capacity is about 5,000 b.t.u., no heat recuperation range—51° to 162°, altitude range to 50,000 ft.—Eaton

AVIATION WEEK, August 8, 1952

Industries, Inc., 100 Staff St., Mendon, Mass.

Cooperation, turbine machine (both pressure and vacuum) on an over 100 delivery order from standard cooperation Model DW114 controls pressure with an accuracy of one-half of one percent.—Goss Hydraulic, Inc., New York International Airport, Jamaica 30, N. Y.

Volvo 23 quenching oil is used to keep high modulus steels and some ferritic steels and ferrite during heat-treating operations. This makes it possible to quench low carbon or low alloy steels

in oil—Shell Oil Co., 50 W. 59th St., New York 20, N. Y.

P5 single clamp is a 10,000-lb-pressure unit with a 2-in. stroke.—Cable Arc Welding Assembly Division, Electro Products, Inc., 2670 E. 61st St., Cleveland 3, Ohio.

Universal shoring machine for form labor, felt, asbestos and similar materials for asbestos shoring system.—Coe Metal Manufacturing Co., Mansfield, Ohio.

Portable cleaner runs high-revolutions to clean electronic and electronic

Still First

in commercial helicopter production...



the **BELL 47G**

... and still powered by



4 out of 5 helicopters under 400 h.p. produced this year will have power by Franklin

AIRCORED MOTORS, INC.
SYRACUSE, N. Y.

Franklin Engine & Co. Inc., 45 Frisco Drive, N. Y. C.
Export Distributors of American Products

**The most complete line of
AIRCRAFT INVERTERS**



Building inverters for regular and special aircraft needs is one of Bendix Red Bull's specialties. That, we offer the widest range of standard inverters plus the ability to design and produce all kinds of special-purpose inverters... including models up to 5000 VA and models for high-temperature, high-altitude applications. For complete details on inverters to meet your needs exactly, write Aircraft Inverter Section, Bendix Red Bull Division, Evansville, IN 5.

Type	INPUT			OUTPUT			V _{CE} at 100% Load	Wattage, W _{CE}	Equivalent to 400 Cycle Output, Watts
	V _{CE}	Current	Watts	V _{CE}	Phase	Watts			
200-01	21.5	—	75	12	12	100%	100%	2000	2000
200-02	21.5	—	75	12	12	100%	100%	2000	2000
200-03	21.5	—	110	12	12	100%	100%	2000	2000
200-04	21.5	—	110	12	12	100%	100%	2000	2000
200-05	21.5	—	110	12	12	100%	100%	2000	2000
200-06	21.5	—	110	12	12	100%	100%	2000	2000
200-07	21.5	—	110	12	12	100%	100%	2000	2000
200-08	21.5	—	110	12	12	100%	100%	2000	2000
200-09	21.5	—	110	12	12	100%	100%	2000	2000
200-10	21.5	—	110	12	12	100%	100%	2000	2000
200-11	21.5	—	110	12	12	100%	100%	2000	2000
200-12	21.5	—	110	12	12	100%	100%	2000	2000
200-13	21.5	—	110	12	12	100%	100%	2000	2000
200-14	21.5	—	110	12	12	100%	100%	2000	2000
200-15	21.5	—	110	12	12	100%	100%	2000	2000
200-16	21.5	—	110	12	12	100%	100%	2000	2000
200-17	21.5	—	110	12	12	100%	100%	2000	2000
200-18	21.5	—	110	12	12	100%	100%	2000	2000
200-19	21.5	—	110	12	12	100%	100%	2000	2000
200-20	21.5	—	110	12	12	100%	100%	2000	2000
200-21	21.5	—	110	12	12	100%	100%	2000	2000
200-22	21.5	—	110	12	12	100%	100%	2000	2000
200-23	21.5	—	110	12	12	100%	100%	2000	2000
200-24	21.5	—	110	12	12	100%	100%	2000	2000
200-25	21.5	—	110	12	12	100%	100%	2000	2000
200-26	21.5	—	110	12	12	100%	100%	2000	2000
200-27	21.5	—	110	12	12	100%	100%	2000	2000
200-28	21.5	—	110	12	12	100%	100%	2000	2000
200-29	21.5	—	110	12	12	100%	100%	2000	2000
200-30	21.5	—	110	12	12	100%	100%	2000	2000
200-31	21.5	—	110	12	12	100%	100%	2000	2000
200-32	21.5	—	110	12	12	100%	100%	2000	2000
200-33	21.5	—	110	12	12	100%	100%	2000	2000
200-34	21.5	—	110	12	12	100%	100%	2000	2000
200-35	21.5	—	110	12	12	100%	100%	2000	2000
200-36	21.5	—	110	12	12	100%	100%	2000	2000
200-37	21.5	—	110	12	12	100%	100%	2000	2000
200-38	21.5	—	110	12	12	100%	100%	2000	2000
200-39	21.5	—	110	12	12	100%	100%	2000	2000
200-40	21.5	—	110	12	12	100%	100%	2000	2000

NOTE: S.C. rated output should be nominal value at 21.5 volts. but all systems designed to operate with 200-75 volts. Input voltage should be within 10% of 21.5 volts.

Institute of Health Policy Studies
University of Southampton
Main Building, Highfield Road, Southampton SO9 5NH, UK

Bendix
The Bend
 EATONTOWN, N. J.

Waco Creek Sales and Service • Export Sales Service International, Inc.
100 E. Washington Ave., Berkeley, Calif. • 100 East 42nd St., New York 17, N. Y.

chemical components. Unit also filters, heats and regulates compressed air to 90 psi, which is recirculated with a non-flammable, non-corrosive and non-polluting solvent certified to military spec—Coblen, Inc. (Caldwell, N.J.).

Interfacial heat transfer surfaces are now applicable to a wide range of various heat transfer experiments including air-to-air, liquid-to-air and liquid-to-liquid.



applications. Sartorius was able to provide greater outer surface and smaller hydrostatic radius—Bath Manufacturing Co., W. Hartford, Conn.

Adjusted for issues not incorporated Scott's argument that provides enough air for 15 min. work inside the suit—Whitely Protective Apparel, Inc., Chicago, Ill.

Vibrations table for electronic tests has 560 cps frequency range, 50 lb max. rated load and 5.2-in. minimum total amplitude—Laser Products, P.O. Box 151, Tarrytown, NY.

Portable spot welder has built-in electronic timing control. Unit delivers 1517,000 amp. at speed of weld.



Thread = 6 in., with 3 to 11 in. variable openings—Rens Machine Tool Co., P.O. Box 112, Chicago, Ill. 10

Dant super pens for compacting powdered metal and ceramics has smooth toggle motion with fast approach to die cavity and fast draw, entry into die—Arnold Chemical, Inc., 1 E. 50th St., New York 22, N.Y.

AVIATION
WEEK

THE MAGAZINE OF AVIATION BUSINESS

Revised: 2011-08-01

Source: *Journal of the American Statistical Association*, 1997, 92, 1039-1052.

张永成、周志峰译，北京：中国文联出版社，2006。

1955

MEMORANDUM TO THE AVIATION INDUSTRY

The tremendous growth of aviation has created a whole new field of needed information services. Today, because of the great expansion of our industry, a publishing task of major importance is the establishment of our industry's first comprehensive annual buyers' guide with a circulation large enough to penetrate the industry's major purchasing influences, domestically and internationally.

November, 1965 will mark the publication of the AVIATION WEEK Buyers' Guide—an annual edition that will answer the long-felt demand of our industry's buyers, in civilian, Air Force and governmental capacities.

Questions are now being mailed to every manufacturer of record engaged in the production and supply of aeronautical products and materials. A year-round research group under editorial supervision has been established to seek out new products, new terminologies—to check and double check the accuracy of all information to be published—the availability and actual production of all items featured.

AVIATION WEEK's annual Buyers' Guide will establish a publishing service unique to our industry. It will be complete and comprehensive—with complete listing of all manufacturers of aeronautical and allied products—not just a token listing; correct and complete addresses; sufficient cross-indexing to locate any product regardless of terminology . . . and most important, the Buyers' Guide format will provide in one complete listing, a simple, easily used method of locating any product. In addition to these important details, the Buyers' Guide will have trade name and distributor listings. These are the factors of completeness—these are the essential features that will make AVIATION WEEK's Buyers' Guide a must for every aviation purchasing influence.

I am sure you will find this annual guide the No. 1 sales and merchandising opportunity for the year-round promotion and advertising of your products, materials and services.

Your AVIATION WEEK representative will gladly give you full details on advertising rates, mechanical specifications, closing dates or any other information that you may desire.

Very truly yours,

Robert W Martus

Robert W. Martin, Jr.
Publisher

gap in Western's system and integrative efforts will take the airline's routes east. Western insists the area it has lost to the west coast of those cities that authorization of Western would not create a significant amount of service from its carrier with the exception of Los Angeles and that the competition from United would be less than that of an other carrier in the case. Western would provide a positive amount of new one-carrier service in addition to flight charters since there are other applicants.

Lifts American Restrictions

Moore also points out that Western is the smallest of the nonaffiliated airlines and that new routes will strengthen its position since the carrier depends on a few high-density routes to support uneconomical operations at the numerous small traffic points on the system.

Several restrictions on American's transcontinental routes would be re-

moved under the carrier's route reallocation. Currently, American must make one stop at Tulsa, Dallas or a point west of those cities on flights between San Francisco and points east of Tulsa or Dallas on Route 4. Service between San Francisco and eastern points on routes 5 and 15 must show that entering but must make no stops.

The airport communities around the restrictions to allow American to operate nonstop flights between San Francisco and Chicago, New York, Boston, Washington and other eastern points.

Moore also recommends American be permitted to operate nonstop between Los Angeles and Detroit and other eastern points.

A restriction on American's transcontinental route which prohibits all coast, operational steps must be lifted by the carrier. This route would permit more efficient routing and dispatching on transcontinental flights.

Continental Plans on Jet Airliners For Los Angeles-Chicago Route

Continental Air Lines plans to operate Lockheed Electra Douglas DC-10s in a commercial service of the Boeing 707 between Los Angeles and Chicago by late 1978 or early 1979 if the Civil Aeronautics Board approves its certificate for the new route. In the meantime, CAL will pick up its option on 15 McDonnell Douglas VC-100s or 15 Lockheed 109W Super Constellation.

The airline expects to spend more than \$40 million in new equipment for the proposed Los Angeles-Detroit-Chicago route, according to Continental's chief executive, Frederick D. Miles.

Leading Candidates

Last week, CAL President Robert F. Lee talked to Jack Elman of DC-10s in a Boeing jet airline and Viscount is in the gate-to-gate 100% of the carrier's base of direction to work out the 540 million is equipment program and then continued in to Los Angeles. In talks with Lockheed Aircraft Corp. and the Douglas Aircraft Co. The schedule did not include a trip to Seattle for negotiations with Boeing Aircraft Co.

On Sept. 4, Lee will fly to Boston with Capital Airlines President J. H. Connelley and F. B. Franklin, CAL vice president of operations, for a second look at the Viscount and to appear with Western Airlines. He is expected the medium haul airline in

England last May and took an option on 17 of the 800.

If Lee settles on the Viscount, he will match the long-range transport now being put into service by Capital and will set up possible on-line connections to the airline's existing proposed interchange with CAL at Chicago.

Delivery of CAL's Viscounts would start in mid 1978.

Expansion Program

Jet and medium transport sales will follow closely on the heels of an expansion and equipment program that includes a new 57 million freight and off-fuel building revealed last week and \$20

million laid out in April for three Conquest 140s and five Douglas DC-6Bs.

Continental will build a new structure on a 54-acre site at Stapleton Airfield headquarters in Denver. Construction is scheduled to begin late this fall, with completion set for early in 1979.

Announcement of plans for the building came shortly after the CAL announced President Miles' route reallocation. Continental spokesman said the structure is not contingent on final Board approval of the new route but admitted that construction may be slowed and the 57-million project broken into stages if the carrier's income is not sufficient.

As planned, the new headquarters will include a two-story brick, concrete and limestone office building with 387,500 square feet of space. A large hall will have 170,000 square feet of space through to house an DC-6Bs and four Conquest 97,500 square feet for shops and maintenance units.

Actual cost of the building will be \$5,714,678, with the balance going for engineering, architectural work and design and financing.

Continental's new new DC-6Bs will be delivered in April, 1977 and put into service on the airline's present eight routes—Denver, Kansas City, Omaha, St. Louis, Dallas-Fort Worth, San Francisco, Los Angeles and New York. The DC-6Bs will be taken into service next year and operated on the local service routes. "Until that time, CAL obtained when it obtained Pan Am's Air Lines."

PAA's Airfreight Up

Pan American World Airways' trans-Atlantic airfreight volume increased to 2,048,000 lb. during the first half of 1978, a 19% gain over the same period last year.

To handle the new business, PAA added a fourth all-cargo flight to its weekly schedule.

Plans were filed to slow down, equal and fast times now through freighter over. Schedules were increased.

"Airborne radio is one of the most advancements made in recent years for commercial flying both from the passenger and pilot viewpoint," Capt. Victor B. Howard, a Pan Am pilot for 11 years told Airline World.

Pan Am is piloting airborne radio in its present of the latest DC-7B and several DC-6B flights from Miami to America's West.

Plans to upgrade the radio system will be completed by the end of the year.

"The airborne radio should speed the time between dispatch and arrival as well as customer convenience," the safety of flight," said Edward C. Bern, Pan Am's vice president for sales and traffic.

Several of them has caused con-

Airborne Radar Speeds Panagra Flights

By G. J. McAllister

Buenos Aires—Pan American Great Airways is actively seeking suitable and successful aircraft for its routes to and from South America.

Effects of the Boeing 707-300 radar system was demonstrated last week in the pre-flight flight of Panagra's DC-7B-100 from Buenos Aires to Lima. The 14,000-mile trip was completed with no discernible problems, although the remaining flight proved to be one of the airline's most rugged terrain and areas of unpredictable storm activity.

The system flight was made in 25 hr, 2 min, a new commercial record. Actual flight time was 18 hr, 2 min. This is a 1-hr faster than the previous best time.

First flight to Lima and the new commercial record was scheduled since Panagra is equipping all new fleet of DC-7Bs and to DC-6Bs with the RDR-1 radar which operates on the "X" band (3-2 cm).

Panagra Vice President and General Manager Douglas Campbell pointed out three advantages:

- Schedule reliability
- Passenger appeal
- Maintenance savings

One of the major difficulties of South American flight operations is the terrain which is a factor in conditions, particularly at night. A permanent service can be maintained only if the airline is able to maintain a high level of service. In addition, when an airline is able to maintain a high level of service, it can maintain a high level of service.

Plans were filed to slow down, equal and fast times now through freighter over. Schedules were increased.

"Airborne radio is one of the most advancements made in recent years for commercial flying both from the passenger and pilot viewpoint," Capt. Victor B. Howard, a Pan Am pilot for 11 years told Airline World.

Pan Am is piloting airborne radio in its present of the latest DC-7B and several DC-6B flights from Miami to America's West.

Plans to upgrade the radio system will be completed by the end of the year.

"The airborne radio should speed the time between dispatch and arrival as well as customer convenience," the safety of flight," said Edward C. Bern, Pan Am's vice president for sales and traffic.

Several of them has caused con-

struction damage to aircraft in South American areas requiring a complete overhaul before they can be used in commercial service. Even relatively minor disturbances may affect sufficient damage to keep an aircraft out of service for a week or two.

Panagra is proud of its 15 years of safety record, a record that can be maintained with the use of airborne radar.

The carrier conducted a year of evaluation flights on the RDR-1 radar in one of its DC-6Bs before a decision was made to equip its DC-7Bs and DC-6Bs.

Panagra selected the "X" band because of best test results. The "X" band has a data basis in accurately determining distance within a specified area. The "C" band has a greater position error.

Operation of a weather radar system depends upon the fact that water vapor, which is suspended in a cloud or as rainfall will reflect a radio beam to an extent dependent upon the concentration of the moisture.

Simple Scope Presentation

A plot with a minimum amount of training can determine the weather conditions quickly because of the planned position indicator (PFI) scope presentation, called an enroute screen. The position indicator and extent of the screen can be judged quickly and a decision made whether to fly around or through a storm area can be made with confidence.

The enroute presentation gives an indication of the location of severe turbulence by noting the size of change in rain intensity. The rate of change is highest, and the turbulence greatest where the highest rain surrounding a dark area is observed. These are the areas to be avoided.

The RDR-1 radar produces a pencil beam which is stabilized for the full range and width of the airplane. Maximum range of the system is 130 miles. A switch on the indicator permits a display of angles of 20, 50 or 150 miles.

The radar system is made up of 120 degrees in either side of Panagra's DC-7B during flight and it is possible to fly the beam to examine other altitudes or to ground terrain mapping purposes.

On the return flight of Panagra's RDR-1 from America's West, it was possible to watch the terrain of the Andes and the flight proceeded from Buenos Aires to Lima. The RDR-1 also has provisions for a ground terrain map to be displayed on the indicator. The RDR-1 also has a provision for a ground terrain map to be displayed on the indicator. The RDR-1 also has a provision for a ground terrain map to be displayed on the indicator.

Several of them has caused con-

the weather ahead through the supplied detection radar scope and it is able to maintain the DC-7B with the RDR-1. A 10-degree radar plot which can make a combined turn without losing altitude.

Total weight of the RDR-1 including antenna indicator, antenna mast, front antenna receiver and control unit, is 3,114 lb.

Penalty Plan Sought For No Show Fares

Industry agreement on a penalty system for no show and late reservation cancellations will be sought by the domestic airlines at a meeting in a special Air Traffic Conference meeting to be held in Chicago this week.

ATC members will consider a penalty plan proposed by a special committee on no show and late reservation cancellations. The committee's recommendations will be presented at the annual meeting last May in Boston (AW May 16 p. 30).

- If the airline's major penalty is a 25% penalty on no show, it will be changed to 25% of the fare for the last leg of the trip, with a \$2 minimum.
- If a passenger cancels or changes his reservation less than 10 days before scheduled departure, he will be assessed 10%, with a minimum of \$5.
- If a passenger has confirmed space he will be required to pick up his ticket 10 days in advance or be 10% of the next day, whichever is higher.

Industry officials report that no show rates are rising from 10% to 15% and the domestic airlines are certain to establish a system for controlling gate-to-gate rates.

Industry officials report that no show rates are rising from 10% to 15% and the domestic airlines are certain to establish a system for controlling gate-to-gate rates.

Fresh Air for Swissair

Swissair is equipping its entire fleet with a new air conditioning system which will be able to remove all bacteria and dust, decreasing the possibility of an outbreak (AW May 25, p. 122). When the device is installed, each airplane will be protected for the last time from bacteria, dust and other air.

The new air to fight against is a small metal cylinder containing filter glass impregnated with P.A. a bactericidal which has the property of removing all bacteria and dust from the air. The device is designed to be replaced at the end of the flight, leaving the atmosphere fresh. The carriage must be in the air as it is moved past by the plane's air conditioning system.



CONTINENTAL'S NEW \$75-MILLION headquarters, to be built at Denver's Stapleton Air field, is shown in the artist's sketch. Thermal bridge (upper right) allows for expansion.

American Disputes Viscount Data

Performance capabilities of the Viscount turboprop transport which Capital Airlines' jet is never last month, have been challenged in American Airlines during the New York-Los Angeles Route Case before the Civil Aeronautics Board. Both of the carriers are involved in the case.

CAB Executive William Wicks, at the request of American Airlines (Los Angeles, Los Angeles), J. H. Connelley, Capital's president, in production. Viscount performance data for consideration at the hearings.

Douglas made by turboprop request with the change that Capital's New York-Washington-Miami Viscount shuttles proposed in the Florida case were in excess of the manufacturer's claim for the Viscount and "certainly misleading." It was pointed out that the schedule gap is more equal to those for the Douglas DC7.

In a previous request for the Capital Viscount specification Douglas drew a gross line from Capital that Capital would forward the schedule to a schedule which it based the Viscount shuttles

Viscount Traffic Gains

Capital Airlines reports an average passenger load factor of 92% for the first 10 days of scheduled service with the Viscount turboprop transport. Since Capital assigned Viscount service July 16, the lowest load factor for the turboprop has been 79% and the highest 96%. This compares with last month's average load factor of 79% with Constellation service over the same area.

in the Florida case. When he asked for the schedule of Constellation, Douglas said the data had not been produced in two weeks here.

Connelley was scheduled to deliver a copy of the specifications relative to the performance of the Viscount 700-D turboprop equipped with the Rolls-Royce Dart 500 and the T10 as proof that had been received from Viscount. He also said that the schedule was up to June 15, 1955.

When the schedule case opened, Eastern Air Lines asked the CAB to equal it to a general comparison of service between the south, Texas and California. CAB asked that Texas-California route proposals be included.

Several airlines objected to expansion of the case, but asked to be included if it was expanded. CAB has decided to limit the case to the California case.

CAB Member Jack Long argued with the majority decision. He points out that American Airlines dominates Texas-California service, and that California shuttles from the north to California are American's main line from Texas to the West Coast.

Long says that "the majority is apparently unwilling to try the case of the competitive service between Texas and California."

"I think it is a great mistake to present any proposals at the expense of the public interest."

Tower Hazard Studied
A special working group to study the conflict between overland and undersea television interests as the use of air space was involved last week by the Joint Industry-Government VLF Shortwave Committee.

The seven-member full-fledged group was organized by Civil Aeronautics Board member and Civil Aeronautics Commissioner Robert E. Lee, co-chairman of the group was directed to make its report by Sept. 15.

The new working group is specifically charged with finding ways to reduce the aircraft tower collision threat. It will coordinate the efforts of two aviation and radio-TV test finding groups which were set up with each other in their final reports to the committee.

and 73,161,489 passengers over the same period last year. Gross revenues for the period rose \$4,938,907, or approximately 6.9% over the second quarter of 1954.

CAB Will Not Expand 2 Interchange Cases

Civil Aeronautics Board has refused to open a general investigation of air service between the north and the west in scheduling requests for expansion of two Texas-California interchange cases.

The prospect of a duplicate of the long, bitter airline service to the west case now alive at CAB began consideration of the general of a formal American-Wide World Airlines' scheduling at Asheville, Tex., and a Continental Air Lines route segment between Houston and San Antonio. The continental request is a part of a Continental Airlines Airline interchange between Houston and California.

When the interchange case opened, Eastern Air Lines asked the CAB to equal it to a general comparison of service between the south, Texas and California. CAB asked that Texas-California route proposals be included.

Several airlines objected to expansion of the case, but asked to be included if it was expanded. CAB has decided to limit the case to the California case.

CAB Member Jack Long argued with the majority decision. He points out that American Airlines dominates Texas-California service, and that California shuttles from the north to California are American's main line from Texas to the West Coast.

Long says that "the majority is apparently unwilling to try the case of the competitive service between Texas and California."

"I think it is a great mistake to present any proposals at the expense of the public interest."

Tower Hazard Studied
A special working group to study the conflict between overland and undersea television interests as the use of air space was involved last week by the Joint Industry-Government VLF Shortwave Committee.

The seven-member full-fledged group was organized by Civil Aeronautics Board member and Civil Aeronautics Commissioner Robert E. Lee, co-chairman of the group was directed to make its report by Sept. 15.

The new working group is specifically charged with finding ways to reduce the aircraft tower collision threat. It will coordinate the efforts of two aviation and radio-TV test finding groups which were set up with each other in their final reports to the committee.

CAB ORDERS

(July 15 to July 17)

GRANTED

Procter American Corp. Air transport to perform two scheduled flights daily between Chicago, Ill., and Santa Ana, California, pursuant to agreement with Western Pacific Airlines.

Transamerica Corp. Air transport to perform one charter flight from New York to Pittsburgh, Pa., on Sept. 15, 1955, for the Western Pacific Airlines, 15 people from Western State High School, Kansas, and Mrs. M. J. M. M.

North American Airlines, Trans National Airlines, Trans American Airways, Hawaiian Airlines, Trans Pacific Airlines, Gulf Air Transport, Air France Group, and Transoceanic Air Transport have an interest in the WCA/ATAA commercial charter interchange.

Los Angeles International Airport and the International Association of Machinists have an interest in the Eastern-California interchange.

Pony Truck Lines an exemption to perform its flights as express and night flights in California to New York from Los Angeles, Pa., Memphis, Tennessee, St. Louis, Mo., and other cities pursuant to the CAB's order to the International Association of Machinists.

Continental Air Lines an exemption to perform its flights as express and night flights in California to New York from Los Angeles, Pa., Memphis, Tennessee, St. Louis, Mo., and other cities pursuant to the CAB's order to the International Association of Machinists.

Los Angeles International Airport and the International Association of Machinists have an interest in the Eastern-California interchange.

Pony Truck Lines an exemption to perform its flights as express and night flights in California to New York from Los Angeles, Pa., Memphis, Tennessee, St. Louis, Mo., and other cities pursuant to the CAB's order to the International Association of Machinists.

Continental Air Lines an exemption to perform its flights as express and night flights in California to New York from Los Angeles, Pa., Memphis, Tennessee, St. Louis, Mo., and other cities pursuant to the CAB's order to the International Association of Machinists.

Los Angeles International Airport and the International Association of Machinists have an interest in the Eastern-California interchange.

Pony Truck Lines an exemption to perform its flights as express and night flights in California to New York from Los Angeles, Pa., Memphis, Tennessee, St. Louis, Mo., and other cities pursuant to the CAB's order to the International Association of Machinists.

Continental Air Lines an exemption to perform its flights as express and night flights in California to New York from Los Angeles, Pa., Memphis, Tennessee, St. Louis, Mo., and other cities pursuant to the CAB's order to the International Association of Machinists.

Los Angeles International Airport and the International Association of Machinists have an interest in the Eastern-California interchange.

Pony Truck Lines an exemption to perform its flights as express and night flights in California to New York from Los Angeles, Pa., Memphis, Tennessee, St. Louis, Mo., and other cities pursuant to the CAB's order to the International Association of Machinists.

Air France 1049Gs

Four-Air France will get the first Lockheed 1049G Super Constellation of its own order into North Atlantic service this month. The aircraft will be delivered by September, flying to 13 scheduled routes of 1049Gs in Air France's trans-Atlantic fleet.

The new transports will be used to replace 1049Gs now in operation, which in turn will replace 749Gs Constellation and 749Gs Constellation in French Air France and French Equatorial Africa.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

With a present equipment Air France carried 780,000 passengers during the first six months of 1955, a 30% increase over the same period last year. The increase in cargo was 3,500 tons, the year's first and last week's cargo was 650,000 tons, a 30% increase over the same period last year.

Pacific Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

Kline-Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

Kline-Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

Kline-Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

Kline-Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

Kline-Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

Kline-Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

Kline-Rite's San Juan Air Terminal was used by 992,829 passengers in the first six months of 1955.

American Airlines and KLM Royal Dutch Airlines are offering part in a new route between the two trans-Atlantic carriers' DC-4s.

North American Wins Reprieve

North American Airlines has been granted a short reprieve from the task of a Civil Aeronautics Board decision to order the carrier out of business (AW-July 11, p. 107).

The Board has now postponed the effectiveness of its order to give North American an opportunity to ask for judicial review.

CAB postponed review of the operating authority of the carrier after a group asked 30 days after a Civil Aeronautics Board decision to order the carrier out of business (AW-July 11, p. 107).

The carrier and its parent company, the North American Airlines, have asked the court to order the carrier out of business (AW-July 11, p. 107).

The carrier and its parent company, the North American Airlines, have asked the court to order the carrier out of business (AW-July 11, p. 107).

The carrier and its parent company, the North American Airlines, have asked the court to order the carrier out of business (AW-July 11, p. 107).

The carrier and its parent company, the North American Airlines, have asked the court to order the carrier out of business (AW-July 11, p. 107).

The carrier and its parent company, the North American Airlines, have asked the court to order the carrier out of business (AW-July 11, p. 107).

The carrier and its parent company, the North American Airlines, have asked the court to order the carrier out of business (AW-July 11, p. 107).

SHORTLINES

Cost Lines Airline, Inc., Ypsilanti, Mich., has been licensed by the Civil Aeronautics Board for non-scheduled charter operations between Ypsilanti and Detroit, Mich., and points in Ontario and Quebec. The authorization is for three years, with aircraft having a maximum load limit of 6,000 lb.

LACSA, Costa Rican airline, on new route from San Salvador, El Salvador, under a reciprocal agreement between the two governments. LACSA could make daily flights weekly at San Salvador or San Jose, Costa Rica.

KLM Royal Dutch Airlines will start construction of the world's largest airport in the Netherlands, near Schiphol, Amsterdam. The airport is designed to accommodate seven B-54s, a DC-7, two C-54s, plus office, stores, a canteen and a hotel.

United Air Lines will expand its facilities at Seattle-Tacoma airport in a \$1,000,000 program which includes a new flight kitchen and a lounge addition.

Western Air Lines has inaugurated service at Santa Fe, N. M., on routes between Minneapolis, St. Paul and Salt Lake City and Denver.

ENGINEERS and DESIGNERS NEEDED

for:

MISSILE GUIDANCE
SYSTEMSSOMEBODY NAVIGATIONAL
COMPUTER SYSTEMSNEW CIVIL AVIATION
PROJECTSJET AND TURBO-PROP
ENGINE CONTROLSAIRCRAFT FIRE
CONTROLS

ON CAREER OPPORTUNITIES IN

Systems Engineering and Analysis
Experimental Engineering
Development Engineering
Project CoordinationDesign Engineering
Product Engineering
Product Evaluation
Field Engineering

AND WE ALSO NEED:

DESIGNERS • CHECKERS • LAYOUT MEN

Positions Are Permanent

Excellent Advancement Opportunities

Every inquiry treated confidentially and given
immediate attention and prompt reply.

WRITE TODAY FOR EMPLOYMENT APPLICATION

Mr. Louis B. Tarkenton
Supervisor of EmploymentAC SPARK PLUG DIVISION
Precision Instrument Plant

GENERAL MOTORS CORPORATION

Milwaukee 2, Wisconsin



is YOUR FUTURE as promising as a HELICOPTER'S?

We think the future of the helicopter is virtually unlimited. Why not make your future just as promising?

SIKORSKY, pioneer helicopter manufacturer, needs . . .

WEIGHTS ENGINEERS
ELECTRICAL ENGINEERS
STRESS ANALYST ENGINEERS
AIRCRAFT DESIGN ENGINEERS

to do important work in the fascinating and fast-growing helicopter field. Expanding military and commercial requirements are a challenge to skilled men—offer excellent opportunities to further your professional status.

Engineers whose abilities or experience qualify them for these responsible positions will enjoy a well-rewarded career with a secure future and many benefits for themselves and their families.

Send a complete resume to: R. E. Austin, Personnel Department

SIKORSKY AIRCRAFT

Bridgeport 1,

Connecticut

AEROPHYSICS ENGINEERS

FOR AUTOMATIC
FLIGHT CONTROLS SYSTEMS
ANALYSIS

Sound aerotherm problems arise for engineers with applicable experience in the control and systems of automatic flight control systems.

The work consists of determining the requirements and performance of an airplane control system on latest type aircraft and missiles. Opportunity exists for the development of new methods and techniques of analysis.

Responsible position with leading design and production of jet-powered automatic flight control systems, space vehicle and missile systems, and other modernized aircraft.

Extensive experience at company or university with automatic systems. An excellent career opportunity.

Send completed resume to:
Employment Manager



LEAR, INC.

11100, N. W.
Grand Rapids, Michigan

ENGINEERS

LONG-RANGE
CONTINUING
OPPORTUNITY
FOR
ELECTRICAL
AND
MECHANICAL

ENGINEERS

AT

OPENINGS EXIST FOR . . .

LIQUID PROPELLANT

ROCKET CONTROLS

ENGINEER

Mechanical or electrical engineer to supervise the research and development of liquid propellant rocket controls, system design, component design, development and testing.

CONTROL ENGINEER

Responsible in engineering design to the final engineering or manufacturing phase of at least three years of experience in design, analysis of liquid control systems. Should be familiar with low-pressure systems methods as applied to feedback control systems. Design experience and scientific experience highly desirable. Activity is in the field of electrical and mechanical control systems including gas turbine engines, jet and rocket engines. Control systems include hydromechanical. The best modern control facility includes an analog computer and an engine simulator.

MAGNETIC AMPLIFIER
SYSTEMS ENGINEER

Responsible for the design, development, analysis and development of magnetic amplifier systems and components. Design and development of magnetic amplifier systems and components. The activity of these positions will be determined by your ability and experience.

Send detailed resume today indicating engineering experience, and salary requirements.

Technical Employment Department S.B.

Bendix Products Division of

Bendix Aviation Corporation

400 North Bendix Drive

South Bend 30, Indiana

We guarantee you an immediate reply.



which do you want?

"Money or the moon?"

It was reaching for the moon which resulted in the development at Martin of one of the most dynamic engineering teams operating in the whole new world of flight systems development.

Most of the people on that team are younger and moving ahead fast. Do you know what's happening today at Martin... and what tomorrow may hold for you here in the fields of aircraft, missiles, rockets, nuclear power and space vehicle development?

Contact J. M. Holliday, Dept. A-8, The Glenn L. Martin Company, Baltimore 5, Maryland.

MARTIN

BALTIMORE • MARYLAND



The Air Traffic Control Problem

The steadily increasing density of air traffic is a grave problem facing both civil and military aviation. Air traffic already has badly overloaded the federal airways system, and its rate of growth is outstripping the pace of technical and political progress in developing new and more efficient traffic control methods.

The traffic itself poses three serious threats to civil aviation:

- **Further restriction of enroute enroute flying** such as the high density traffic now monthly established in the Washington, D. C., terminal area.
- **Economic limitation** on the growth of airline revenues because of the inability to move more aircraft in and out of busy traffic terminals, particularly in bad weather.

Air Defense Hazard

For the military, air traffic control limitations now interfere with and seriously hamper efficient performance of Air Defense and Strategic Air Command missions. For example, many all-weather jet fighters defending New York City have to "scramble" 70 miles out to sea at low altitude before they can do a maximum climb to intercept altitude in order to avoid a heavily-traveled federal airspace. The heavy volume of military training and of off-airways flying now makes it necessary to control traffic in large areas and not just along the narrow airways bands.

For both military and civil aviation, the combination of increasing traffic and a DC-3 era traffic control system create a terrible safety hazard. Military air assets are becoming more frequent. Air Transport Association use a "surround" survey for several months recently and heard airline pilots reporting an average of four "near misses" daily.

Not long ago two Strategic Air Command B-47 formations collided through each other inadvertently at night in a head on pass. In the gloom and at the 1,200 mph closing speed, the formations had no warning. Only extreme good luck prevented anything more serious than bent jet engine pods and clipped tail fins.

Airline pilots flying on VOR radials, 15 degrees apart, have found themselves on collision courses when approaching terminal areas.

There appear to be three trends that offer some

immediate improvement in air traffic control safety and efficiency:

- **Increased use of radar**, both for large area and en route control, as well as in the final approach zone. The integration of USAF's air defense radar system and the development of a joint military and airborne radar transponder will do much to speed efficient radar traffic control.
- **Better air-to-ground communications.** The VHF frequencies are badly clogged now. With the high approaches of modern transports, it is not unusual for an airline pilot trying to contact Washington approach control to be blocked out by transmissions on the same frequency at Cleveland. Remote VHF stations, as now used in the New York area, are a help, but it seems likely that the airlines will have to give up many of their company radio frequencies to allocate this problem. Military radio frequencies to UHF also will help.
- **Better situation for both military and civil aircraft.** At the 40,000-ft altitudes where military jets operate, pressure altimeters are not sufficiently accurate. On civil aircraft at lower altitudes the varieties of pressure ports, depending upon the terrain, for altimeters produce cockpit instrument variations that further complicate the altitude separation problem.

Action Urgently Needed

But even more acute than any of these specific points is the need for a unified approach to modernizing the federal airways system and to backing the best technical developments available. The establishment and operation of the federal airways system is the legal responsibility of the Civil Aeronautics Administration. In the past year, the CAA airways operations have drifted in two currents of technical obsolescence and bureaucratic lethargy.

What little progress was made usually came out after military and airline prodding. A much more vigorous approach to the grave problem of air traffic control is necessary now if aviation is to avoid the tragic consequences of some mid-air collisions, economic strangulation of airline revenues and blunted efficiency of Strategic Air Command and Air Defense Command operations.

—Robert Holt

Building, not avoiding, the difficult relays

one phase of LEACH leadership

Some firms share unusual problems, deal only with standard needs — the ones with no design challenge. At Leach Relay Division, on the other hand, we are interested in the unusual. And we're particularly well equipped to handle your complex relay problems, because we can call on the specialized talents of our three companies — all operating under the Leach Corporation's combined responsibility. Here, for example, are three long-standing aircraft problems and the Leach Relays — each a complete, turnkey, tested control package — that solved them...



ON THE GROUND — aircraft phased ground power into main aircraft damage LEACH'S ANSWER... 3203 Photo-Suspension Relay, which includes a 2-phase still larger motor and control switches. Upon the predetermined phase sequence is applied at normal voltage, the relay will not allow the main contractor to close

IN THE AIR... relays must operate from low-level voltages (e.g., 12 volt-ni-ni-ni, subminiature tubes, small ship tings) and shock resistance in vital LEACH'S ANSWER... 3202, a combination of relay and magnetic amplifier, is sensitive to 1 millivolt, is immune to shock as great as 50 g. In addition it is compact and light

ON COURSE... gyro compass drift if voltage input drops, but the lock EMF they generate holds normal relays closed for 15-20 minutes LEACH'S ANSWER... 3217 Close-Differential Relay, a combination of magnetic amplifier, resistor, and relay which senses the pilot of any drop as small as 5 volts

LEACH

LEACH RELAY DIVISION
PLANE GENERATOR DIVISION
INLET AIRFLOW POWER DIVISION

CORPORATION / LEACH RELAY DIVISION

3515 ANSHIM BOULEVARD, LOS ANGELES 3, CALIFORNIA

SEVEN INDUSTRIES BY THE LAKESIDE OF THE LAKE ON THE GROUND IN THE AIR

RESISTOR BRIDGES AND REPRESENTATIONS IN MINORAL CASES OF U.S. AND CANADA

to insure your system performance

Servomechanisms' versatile line of Transducers are *proven* components. Thousands of these precision-built standard and semi-standard components have been produced and are used in Servomechanisms' own sub-systems for many of today's most advanced fighter aircraft. In addition, they are being specified in experimental and prototype aircraft and missiles of tomorrow.

These massed-produced transducers have met all applicable MIL and USAF specifications. Outstanding features include: repeatability of performance, ease of maintenance, complete interchangeability and *maximum* reliability.

Servomechanisms' proven ability to *anticipate* and *interpret* our customers' needs, to *design* to specifications, to *produce* in quantity and to *follow-up* throughout the life of the delivered equipment, all add up to a *complete service*.

SERVOMECHANISMS' TRANSDUCERS ARE USED IN CONJUNCTION WITH THESE SERVOMECHANISMS' SUB-SYSTEMS.



MASTER AIR DATA COMPUTER

Provides a single coordinated source for input information required by navigation, fire control, and flight control systems.



ANGLE OF ATTACK COMPUTER

Solves continuously and simultaneously the mathematical equations for angle of attack of an aircraft.



MACH COMPUTER

Provides an output voltage or shaft rotation proportional to the function of Mach number by mechanically comparing static and differential pressure



PRESSURE TRANSDUCERS

For converting static and differential pressure into suitable electrical signals.




ACCELEROMETER

For converting acceleration, normal to its mounting surface, into suitable electrical signals.



RELATIVE WIND TRANSDUCERS

Both self powered and servo driven types available for sensing changes in airstream direction.



Write for data
brochures
on Servomechanisms'
Transducers.

Servomechanisms
INC.

Eastern Division: Post and Stewart Avenues, Westbury, New York
Components Division: 625 Main Street, Westbury, New York
Western Division: 12500 Aviation Blvd., Hawthorne, California
Canadian Subsidiary: Industrial Electronics of Canada Ltd.
83 Torborrie Road, Toronto 15, Ontario, Canada